



SUMMIT UTILITRUCK



Shown With Options

Driven to work, there's a Summit Utilitruck for the college campus, the park system, the military base or the industrial complex. And, with zero emissions your Summit Utilitruck is even friendly to indoor environments.

Engineered for safety, every Summit Utilitruck is equipped with 4 wheel hydraulic brakes, an AC powered drive system, automotive lighting, controls and steering.

The Summit Utilitruck is available as a NEV which is street legal on roads with posted speed limits up to 35 mph. Frequently used in commercial fleets, you can rest assured the Summit Utilitruck will also have a positive impact on your bottom line.



1



2



3

- 1 Popular Ladder Rack Option
- 2 Folding Side Panels
- 3 2nd Row Seat



COLUMBIA


BUILT FOR WORK



SUMMIT UTILITRUCK

Dimensions

Step Height:	12.5 in.
Load Bed Height:	26 in.
Ground Clearance:	7.5 in



Performance

	SU5-SN	SU5-LN
Max Speed Forward:	25 MPH	
Turning Radius:	Curb to Curb - 247 in.	Curb to Curb - 356 in.
Range ¹ :	Up to 40 miles	

Weight & Capacity

Vehicle Weight :	1,600 lbs.	1,750 lbs.
GVWR	2,600 lbs.	3,000 lbs.
Towing Capacity:	1,500 lbs.	

Power Train

Motor:	48-Volt, AC Induction, NEMA class H temperature rated
Horsepower:	19 HP
Batteries:	Eight, 6 volt, 232 amp hour, 122 minute, deep cycle
Charger:	On-board, micro-processor controlled, fully sealed, global, 100-230 VAC, 50/60 HZ
Controller Type:	Programmable, solid state, reduced speed reverse with diagnostic LED & calibrator interface
Controller Rating:	450 amp
Motor Braking Mode:	Regenerative and pedal proportional braking with top speed limiting
Directional Control:	Fingertip directional control selection
Drive Unit/Differential:	Direct drive, oil bath, helical gears, Automotive style differential, drive ratio 10.37:1

Body

Passenger Capacity:	Two with up to six (optional 2nd row seat and rear facing seat)
Seating:	Adjustable driver seat, Fixed passenger seat, Covered in marine grade vinyl with armrests
Body:	Front - Rhino-Tuff™ molded polymer Mid/Rear - Aluminum
Lighting:	Dual high/low beam headlights, Taillights, Brake lights, Self-canceling turn signals, Emergency flashers
Accessories:	Uniquely keyed in-column keyswitch, Forward & reverse selector, Multi-functional clear view display w/BDI, Speedometer, Horn, Reverse warning alarm, Hour meter, Cup holders, Storage compartments, Comfort grip steering wheel, Automotive lighting package, Windshield, Mirrors, Hard top roof, Reflectors, Dual DC/DC converters, 2-pt Seat belts

Chassis

Frame:	High strength steel channel rail "ladder-style" frame, electrostatically powder coated
Steering:	Automotive rack and pinion
Brakes:	4 Wheel hydraulic, front discs, rear drums, automatic parking brake
Suspension:	Front - Double A arm Independent coil spring over shock absorbers Rear- Independent leaf springs with rubber helper springs
Tires:	205/65-10 10 ply DOT rated tire

Features, options, specifications, color availability and model designation are subject to change without notice. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you order includes the equipment you require.

¹ Range will vary depending on temperature, grade, payload and driving style. | Rated Capacity Includes personnel, cargo, options and accessories.

All specifications are subject to change without notice.

Columbia Vehicle Group, Inc.

A Nordic Group Company | Business Ventures Since 1947

1115 Commercial Ave. Reedsburg, WI 53959
columbiavehicles.com



COLUMBIA



TOMBERLIN



SUMMIT UTILITRUCK

RATED CAPACITY
up to 1,500 lbs.

UP TO 4 PASSENGERS

MAX SPEED FORWARD
up to 19 MPH

TOW
up to 1,500 lbs.



Shown With Options

Driven to work, there's a Summit Utilitruck for the college campus, the park system, the military base or the industrial complex. And, with zero emissions your Summit Utilitruck is even friendly to indoor environments.

Engineered for safety, every Summit Utilitruck is equipped with 4 wheel hydraulic brakes, an AC powered drive system, automotive lighting, controls and steering.



- 1 Hard Door Cab Option
- 2 Aluminum Van Enclosure Option
- 3 Utility Strobe Light



COLUMBIA


BUILT FOR WORK



SUMMIT UTILITRUCK

Dimensions

Step Height:	12.5 in.
Load Bed Height:	26 in.
Ground Clearance:	7.5 in



Performance

	SU5-S	SU5-L
Max Speed Forward:	19 MPH	
Turning Radius:	Curb to Curb - 247 in.	Curb to Curb - 356 in.
Range ¹ :	Up to 40 miles	

Weight & Capacity

Vehicle Weight :	1,500 lbs.	1,650 lbs.
Rated Capacity ² :	1,000 lbs.	1,500 lbs.
Towing Capacity:	1,500 lbs.	

Power Train

Motor:	48-Volt, AC Induction, NEMA class H temperature rated
Horsepower:	19 HP
Batteries:	Eight, 6 volt, 232 amp hour, 122 minute, deep cycle
Charger:	On-board, micro-processor controlled, fully sealed, global, 100-230 VAC, 50/60 HZ
Controller Type:	Programmable, solid state, reduced speed reverse with diagnostic LED & calibrator interface
Controller Rating:	450 amp
Motor Braking Mode:	Regenerative and pedal proportional braking with top speed limiting
Directional Control:	Fingertip directional control selection
Drive Unit/Differential:	Direct drive, oil bath, helical gears, automotive style differential, drive ratio 16.77:1

Body

Passenger Capacity:	Two with up to six (optional 2nd row seat and rear facing seat)
Seating:	Adjustable driver seat, Fixed passenger seat, Covered in marine grade vinyl with armrests
Body:	Front – Rhino-Tuff™ molded polymer Mid/Rear – Aluminum
Lighting:	Dual high/low beam headlights, Taillights, Brake lights, Self-canceling turn signals, Emergency flashers
Accessories:	Uniquely keyed in-column keyswitch, Forward & reverse selector, Multi-functional display w/BDI, Horn, Reverse warning alarm, Hour meter, Cup holders, Storage compartments, Comfort grip steering wheel, Automotive lighting package, Reflectors, DC/DC converter

Chassis

Frame:	High strength steel channel rail "ladder-style" frame, electrostatically powder coated
Steering:	Automotive rack and pinion
Brakes:	4 Wheel hydraulic, front discs, rear drums, automatic parking brake
Suspension:	Front – Double A arm Independent coil spring over shock absorbers Rear– Independent leaf springs with rubber helper springs
Tires:	205/65-10 10 ply DOT rated tire

Features, options, specifications, color availability and model designation are subject to change without notice. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you order includes the equipment you require.

¹ Range will vary depending on temperature, grade, payload and driving style. | ² Rated Capacity Includes personnel, cargo, options and accessories.

All specifications are subject to change without notice.

Columbia Vehicle Group, Inc.

A Nordic Group Company | Business Ventures Since 1947

1115 Commercial Ave. Reedsburg, WI 53959
columbiavehicles.com



COLUMBIA



TOMBERLIN