

TRUCKEE TAHOE AIRPORT DISTRICT


HANGAR 2

STATE MAP:



STATE OF CALIFORNIA

TRUCKEE MAP:




TRUCKEE TAHOE AIRPORT



VICINITY MAP:

NOT TO SCALE



10356 Truckee Airport Rd
Truckee, CA 96161

PROJECT No.: 2013700-171696.01

SHEET INDEX

GENERAL	
G-001	COVER SHEET
G-011	CODE ANALYSIS SCHEDULES
G-021	LIFE SAFETY PLANS
G-101	PHASING PLANS
CIVIL	
C-101	SITE PLAN
C-102	UTILITY PLAN
C-103	GRADING AND DRAINAGE PLAN
STRUCTURAL	
S-001	STRUCTURAL NOTES
S-002	STRUCTURAL NOTES
S-101	FOUNDATION PLAN
ARCHITECTURAL	
A-001	NOTES & SYMBOLS
A-101	FIRST FLOOR PLAN
A-102	MEZZANINE PLAN
A-103	ROOF PLAN
A-121	FIRST FLOOR CEILING PLAN
A-122	HANGAR REFLECTED CEILING PLAN
A-141	EXTERIOR ASSEMBLIES & PARTITION TYPES
A-201	EXTERIOR ELEVATIONS
A-202	EXTERIOR ELEVATIONS
A-203	EXTERIOR 3D REPRESENTATIONS
A-301	BUILDING SECTIONS
A-302	BUILDING SECTIONS
A-311	WALL SECTIONS
A-312	WALL SECTIONS
A-601	SCHEDULES
A-602	WINDOW, CURTAIN WALL AND STOREFRONT ELEVATIONS
ELECTRICAL	
E-010	ELECTRICAL SITE PLAN
E-121	FIRST FLOOR LIGHTING PLAN
E-122	MEZZANINE PLAN - LIGHTING
E-601	SCHEDULES



Mead & Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS
SHEET CONTENTS
COVER SHEET

SHEET NO.:


G-001

APPLICABLE CODES AND DESIGN CRITERIA		
Project Name and Location: Truckee Tahoe Airport (TRK) Hangar 2 Replacement Truckee Tahoe Airport District Truckee, CA		
Applicable Design Criteria and Codes:		
Building Code: California Building Code 2016 (IBC 2015) California Code of Regulations Title 24, Part 2, Volumes 1 & 2		
Plumbing Code: California Plumbing Code 2016 (UPC 2015) California Code of Regulations Title 24, Part 5		
Mechanical Code: California Mechanical Code 2016 (UMC 2015) California Code of Regulations Title 24, Part 4		
Electrical Code: California Electrical Code 2016 (NEC 2014) California Code of Regulations Title 24, Part 3		
Fire/Safety Code: California Fire Code 2016 (IFC 2015) California Code of Regulations Title 24, Part 9		
Accessibility Code: California Building Code 2016 (Chapter 11B) California Code of Regulations Title 24, Part 2		
Energy Code: California Energy Code 2016 California Code of Regulations Title 24, Part 6		
Green Building Standards: California Green Building Standards Code 2016 California Code of Regulations Title 24, Part 11		
NFPA 409 Fire Protection Requirements for Aircraft Hangars		
Construction Type		
NFPA 220 Table 4.1.1 CBC Type IIB = Type II (000)		
Aircraft Hangar Group		
NFPA 409 Section 4.1.1		
Group III	Maximum	Actual
Aircraft access door height	28 ft.	22 ft.
Single fire area	12,000 s.f.	11,250 s.f.
Clear Space Distance at Exterior Perimeter of Hangar Building		
	Minimum	Actual
NFPA 409 Table 8.2.1, Type II (000)	50 ft.	66 ft. (min)
Construction		
NFPA 409 Section 8.1.1 Construction may be of any type specified in NFPA 220		
Fire Rating		
NFPA 409 Section 8.2.2 Partitions and ceilings separating aircraft storage & serving areas from other areas such as shops, offices and parts storage areas shall have at least a 1-hour fire resistance rating		


FIRE PROTECTION AND LIFE SAFETY ANALYSIS				
Building Occupancy Classifications				
CBC Section 303.4: Assembly Group A-3 (Community Halls - Meeting Space)				
CBC Section 304.1: Business Group B (Offices, Commercial Kitchens not associated with restaurants)				
CBC Section 311.2: Moderate-hazard storage, Group S-1 (Aircraft Hangar-storage and repair)				
Construction Type				
CBC Table 601				
Type IIB				
Sprinklered: Yes				
Building Area				
CBC Table 506.2:	Allowable	Actual (1st flr)	Actual (2nd flr)	Ratio
Group A-3 / IIB / SM	28,500 s.f.	1,260 s.f.		0.04
Group B / IIB / SM	69,000 s.f.	4220 s.f.		0.06
Group S-1 / IIB / SM	52,500 s.f.	11,250 s.f.		0.22
		16,425 s.f.		0.32
Frontage Increase				
CBC Section 506.2.1: Minimum Frontage. (W = 30)				
Width limit exceeds 30 ft. in accordance with Section 506.3.2, therefore W shall equal 30				
CBC Section 506.3.3: Frontage increase				
Building Height and Number of Stories				
CBC Table 504.3: Type IIB Construction	Group A-3	Group B	Group S-1	
Allowable (Sprinklered)	75'	75'	75'	
Actual	36'			
CBC Table 504.4: Type IIB Construction				
Allowable (Sprinklered w/o area increase)	3	4	3	
Actual	1			
Occupancy Separations				
CBC Table 508.4 (fully sprinklered)		Group A	Group B	Group S-1
	Group A	-	1 hr	1 hr
	Group B		-	
	Group S-1			-
Fire Resistive Requirements for Building Elements				
CBC Table 601, Type IIB Construction				
Structural Frame:	0 hr			
Bearing Walls				
Exterior:	0 hr			
Interior:	0 hr			
Interior Nonbearing Walls and Partitions:	0 hr			
Floor Construction:	0 hr			
Roof construction and secondary framing:	0 hr			
Fire Resistive Requirements for Exterior Walls Based on Separation Distance				
CBC Table 602 - Exterior Nonbearing Walls and Partitions				
Fire separation distance = X	Groups A, B, S-2		Group S-1	
X < 5 ft	1 hr		2 hr	
5 ft ≤ X < 10 ft	1 hr		1 hr	
10 ft ≤ X < 30 ft	1 hr		1 hr	
X ≥ 30 ft	0 hr		0 hr	
Fire Walls				
CBC 706 - Fire wall rating	Groups A, B, S-1			
	3 hr			
Termination at exterior wall: CBC 706.5				
Termination at roof sheathing: CBC 706.6				
Interior Finishes: Walls and Ceilings				
CBC Table 803.11				
Interior Wall and Ceiling Finish for Exit Enclosures and Exit Passageways: Class C (Sprinklered)				
Interior Wall and Ceiling Finish for Corridors: Class C (Sprinklered)				
Interior Wall and Ceiling Finish for Rooms and Enclosed Spaces: Class C (Sprinklered)				
Interior Finishes: Floors				
CBC Section 804				
Interior Floor Finish for All Floor Coverings: Class I or II				

FIRE PROTECTION AND LIFE SAFETY ANALYSIS, CONTINUED			
Occupant Load			
CBC Table 1004.1.1			
Aircraft hangars: 500 s.f. /occ.			
Assembly - Concentrated (Meeting Room): 15 s.f. /occ.			
Business areas: 100 s.f. / occ.			
Kitchens, commercial: 200 s.f. / occ.			
Function / Floor	Area	Occupants	
Meeting room	1,260	84	
Offices	3,643	37	
Kitchen (prep)	253	2	
Hangar	11,250	23	
1st Floor Mech/Elect areas	323	2	
Capacity of Means of Egress			
CBC Section 1005	Stairs 0.3 inches	Other 0.2 inches	Provided
Meeting Room		22.6 in.	108 inches
Offices		87.1 in.	108 inches
Hangar		3.2 in.	108 inches
Common Path of Travel			
CBC Table 1006.2.1	Groups A	Group B	Groups S
Max. occupant load	49	49	29
Single exit / common path of egress	75'	100'	100'
Exit Access Travel Distance			
CBC Table 1017.2	Groups A & S-1	Group B	
Fully sprinklered	250'	300'	
Minimum Corridor Width			
CBC Table 1020.2			
No Exceptions	44 inches		
Dead-end Corridor Distance			
CBC Section 1020.4			
Group A, sprinklered	20 feet		
Groups B & S, sprinklered	50 feet		
Fire Extinguishers, General			
NFPA 10			
Accessibility Requirements			
The design for this project incorporates the accessibility requirements of CBC Chapter 11B			

C:\Revit Local\2013\700-171696.01-A-CENTRAL-2019.marc.godina.rvt 3/22/2019 9:02:03 AM



TRUE PLAN NORTH NORTH
1
3/32" = 1'-0"
FIRST FLOOR PLAN - CODE & LIFE SAFETY



TRUE PLAN NORTH NORTH
2
3/32" = 1'-0"
MEZZANINE PLAN

CODE PLAN LEGEND:

- | | | | |
|---------------------------------|--|---|---------------------------|
| 6
XX"
XX" | OCCUPANT LOAD (OR MAX. CAPACITY)
OCCUPANT LOAD FACTOR
REQ'D WIDTH
PROVIDED WIDTH | | B OCCUPANCY |
| → | EXIT DISCHARGE | | A-3 OCCUPANCY |
| ◆◆ | 1 HR RATED WALL | | S-1 OCCUPANCY |
| F.E.
⊕ | FIRE EXTINGUISHER - WALL MOUNTED | → | PATH OF EGRESS |
| F.E.C.
⊕ | FIRE EXTINGUISHER - CABINET | ⊗ | WALL MOUNTED EXIT SIGN |
| SF RM OCC
EXITS 1 OLF RM TYP | OCCUPANCY SQUARE FOOTAGE
NUMBER OF OCCUPANTS
OCCUPANCY TYPE
OCCUPANT LOAD FACTOR
NUMBER OF EXITS | ⊗ | CEILING MOUNTED EXIT SIGN |

Mead & Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project, except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS
SHEET CONTENTS
LIFE SAFETY PLANS

SHEET NO.:

G-021

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN


NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS
SHEET CONTENTS
PHASING PLANS

SHEET NO.:


G-101



TRUE PLAN
NORTH NORTH
1
1/8" = 1'-0"

PHASING NOTES:

- THE INTENT OF THE PROJECT IS THAT ALL STRUCTURES ARE BUILT AT ONCE; HOWEVER, DUE TO POTENTIAL FUNDING RESTRICTIONS PRICING SHALL BE PROVIDED W/ SEPARATE LINE ITEMS AS FOLLOWS:
 - PHASE 1 - HANGAR BUILDING
 - PHASE 2 - OFFICE BUILDING
- FURNITURE IS SHOWN FOR REPRESENTATION PURPOSES ONLY. NIC.
- IN THE EVENT ONLY PHASE 1 - HANGAR BUILDING IS INITIALLY CONSTRUCTED, EXTERIOR FINISH OF WEST HANGAR WALL SHALL BE:
 - EXTERIOR ASSEMBLY 2/A-141 TO 7'-4" AFF WITH ADHERED STONE SILL
 - WALL ASSEMBLY 4/A-141 THE REMAINDER OF THE WALL.




PLAN

SCALE: 1" = 20'

LEGEND


ABANDON UTILITY LINE

ABANDON UTILITY STRUCTURE



PLAN

SCALE: 1" = 20'



GRAPHIC SCALE

20 0 10 20

1 INCH = 20 FEET

Mead
& Hunt

Mead & Hunt, Inc.
2440 Deming Way
Middleton, WI 53562
phone: 608-273-6380
meadhunt.com

AUERBACH

ENGINEERING CORP

BOX 5399 • 645 W. LAKE BLVD. • TAHOE CITY • CALIFORNIA • 96145
VOICE (530) 581-1116 • FAX (530) 581-3162
WWW.AUERBACHENGINEERING.COM

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

IRUCKEE | AHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd

ISSUED

SCHEMATIC DESIGN DRAWING
FOR INFORMATION ONLY
NOT FOR CONSTRUCTION

SH NO.: 2013700-171696.01
 DATE: March 22, 2019
 DESIGNED BY: NC/AZ
 DRAWN BY: AZ
 CHECKED BY: RJM

DO NOT SCALE DRAWINGS


UTILITY PLAN

HEET NO.:

C-102


LEGEND

- ABANDON UTILITY LINE
- ABANDON UTILITY STRUCTURE



PLAN

SCALE: 1" = 20'



Mead & Hunt
Mead & Hunt, Inc.
2440 Deming Way
Middleton, WI 53562
phone: 608-273-6380
meadhunt.com

AUERBACH
ENGINEERING CORP
CIVIL ENGINEERING • LAND SURVEYING • ENVIRONMENTAL PLANNING
PROGRAM MANAGEMENT AND PLANNING
PO BOX 0389 • 845 W. LAKE BLVD. • TAHOE CITY • CALIFORNIA • 96145
VOICE (530) 381-1118 • FAX (530) 381-3192
WWW.AUERBACHENGINEERING.COM

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

**TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2**
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED

SCHEMATIC DESIGN DRAWING
INFORMATION FOR PRICING ONLY
NOT FOR CONSTRUCTION

M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: NC/AZ
DRAWN BY: AZ
CHECKED BY: RJM

DO NOT SCALE DRAWINGS

SHEET CONTENTS
GRADING AND
DRAINAGE PLAN

SHEET NO.:

C-103

FOUNDATION NOTES

- F-1. FOOTING SUBGRADES SHALL BE CLEAN AND FREE OF DEBRIS, STANDING WATER, AND LOOSE SOIL.
- F-2. ALL COLUMN FOOTINGS ARE TO BE CENTERED UNDER COLUMN CENTERLINES, UNLESS INDICATED OTHERWISE.
- F-3. THE FOUNDATION CONTRACTOR SHALL FULLY REVIEW UNDER-GROUND PLUMBING DRAWINGS AND SHALL COORDINATE WITH THE UNDER-GROUND PLUMBING CONTRACTOR TO DEPRESS FOOTINGS AND PROVIDE PIPE SLEEVES THROUGH FOUNDATION WALLS AS NECESSARY TO ACCOMMODATE PLUMBING LINES OR TRAPS WHICH PENETRATE CONCRETE FOOTINGS OR FOUNDATIONS.
- F-4. PROVIDE PVC SLEEVES THROUGH FOUNDATION WALLS/FOOTINGS FOR PIPE, CONDUIT, AND CABLE PENETRATIONS, INCLUDING ELECTRICAL GROUNDING SYSTEM CABLES. SEE APPROPRIATE DRAWINGS FOR LOCATIONS/SIZES. PLACE SLEEVES IN LOCATIONS TO AVOID DISPLACING REINFORCING STEEL.
- F-5. REFER TO ELECTRICAL DRAWING SITE LIGHTING FOR POLE BASES. SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR.
- F-6. COORDINATE WITH ARCHITECTURAL AND CIVIL DRAWINGS FOR MISCELLANEOUS FOUNDATIONS NOT SHOWN ON STRUCTURAL DRAWINGS.
- F-7. CONTROL JOINTS IN THE CAST-IN-PLACE CONCRETE FOUNDATION WALLS SHALL BE PLACED AT SPACING NOT TO EXCEED 20' O.C. OR AS LOCATED PER DRAWINGS AND SHOULD ALIGN WITH MASONRY CONTROL JOINTS WHERE APPLICABLE. SEE DETAIL SHEETS FOR CONTROL JOINT DETAILS. PROVIDE VERTICAL "V" GROOVE AT ALL CONSTRUCTION AND CONTROL JOINTS. CONTRACTOR SHALL SUBMIT PLANS OF JOINT LOCATIONS FOR APPROVAL.
- F-8. A LEAN CONCRETE MUD SLAB 2" TO 3" THICK SHALL BE USED IN THE FOOTING EXCAVATION IF THE BOTTOM OF THE EXCAVATION TENDS TO BECOME MUDDY AND SOFT DUE TO CONSTRUCTION ACTIVITY. LEAN CONCRETE SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2000 PSI.
- F-9. COORDINATE GROUNDING REQUIREMENTS FOR FOUNDATION/FOOTING REINFORCING STEEL WITH ELECTRICAL DRAWINGS. COORDINATE INSTALLATION OF GROUNDING WIRES/EQUIPMENT WITH ELECTRICAL CONTRACTOR PRIOR TO CASTING CONCRETE. REFER TO NOTE CR-1 FOR ADDITIONAL INFORMATION.
- F-10. SEE TYPICAL SLAB-ON-GRADE DETAILS FOR SLAB AND SUB-BASE REQUIREMENTS. THESE WILL BE TYPICAL THROUGHOUT UNLESS NOTED OTHERWISE.

- ## MASONRY NOTES

- ## GENERAL NOTES


- MATERIAL PROPERTIES (U.N.O.)**
COMPRESSIVE STRENGTH - $F'_c = 4 \text{ KSI}$
CONCRETE REINFORCEMENT - $F_y = 60 \text{ KSI (A615 GR 60)}$
- CR-1. PROVIDE HOT/COLD WEATHER PROCEDURES AND PROTECTION IN ACCORDANCE WITH ACI RECOMMENDATIONS AND PROJECT SPECIFICATIONS.**
- CR-2. ALL CONCRETE DESIGN AND CONSTRUCTION SHALL CONFORM WITH THE LOCAL BUILDING CODE REQUIREMENTS AND THOSE OF THE FOLLOWING STANDARDS (LATEST EDITION):**
 "ACI 318, BUILDING CODE REQUIREMENTS FOR REINFORCED CONC."
 "ACI 315, DETAILS AND DETAILING OF CONCRETE REINFORCEMENT"
 "ACI 301, SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BLDGS."
 "ACI 307, RECOMMENDED PRACTICE FOR CONCRETE FORM WORK"
- CR-3. REINFORCEMENT SHALL BE DETAILED IN ACCORDANCE WITH ACI 315.**
- CR-4. ALL REINFORCEMENT BARS SHALL BE FABRICATED IN ACCORDANCE WITH THE LATEST CRSI MANUAL OF STANDARD PRACTICE AND SHALL BE CLEAN AND FREE OF GREASE AND SCALING RUST.**
- CR-5. SEE SECTION 033000 OF SPECIFICATIONS FOR INFORMATION REGARDING CONCRETE MIX DESIGN, TESTING, MATERIALS, AND ADMIXTURES.**
- CR-6. CONCRETE REINFORCEMENT PROTECTION/CLEAR COVER, U.N.O.:**
- | | |
|------------------------|--------|
| FOOTINGS: | |
| BOTTOM & SIDES | 3" |
| TOP | 2" |
| WALLS: | |
| EXTERIOR EXPOSURE | 2" |
| INTERIOR EXPOSURE | 1" |
| BEAMS/COLUMNS: | |
| OVER TIES OR STIRRUPS | 1 1/2" |
| ELEVATED SLABS: | |
| | 1" |

- EW-1. REFERENCE SECTION 003132 - GEOTECHNICAL DATA AND SECTION 312010 - EARTH MOVING FOR DEFINITION OF MATERIALS AND COMPACTION REQUIREMENTS.
- EW-2. REFERENCE SECTION 003132 - GEOTECHNICAL DATA AND SECTION 312010 - EARTH MOVING FOR REQUIREMENTS FOR EXCAVATION AND CONTROL OF SURFACE WATER AND GROUND WATER.
- EW-3. UNLESS NOTED OTHERWISE, THE CONTRACTOR SHALL RETAIN AN INDEPENDENT, QUALIFIED GEOTECHNICAL ENGINEERING FIRM/TESTING AGENCY TO IDENTIFY AREAS OF POOR SOILS, TO MONITOR PROPER SUBGRADE PREPARATIONS AND TO OVERSEE AND TEST THE PLACEMENT OF COMPACTED FILL MATERIAL.
- EW-4. ALL SUBTERRANEAN STRUCTURES, UTILITIES, PIPING, ETC. IN THE AREA OF EXCAVATIONS SHALL BE LOCATED AND MARKED BY CONTRACTOR PRIOR TO EARTH REMOVAL WORK. CONTRACTOR SHALL MAINTAIN MARKERS UNTIL EXCAVATION ACTIVITIES HAVE CEASED.
IF UNDERGROUND UTILITY CONFLICTS ARE DISCOVERED BEFORE OR ENCOUNTERED DURING EXCAVATION, NOTIFY THE ARCHITECT/ENGINEER IMMEDIATELY.
- EW-5. BEFORE PLACING FOOTINGS, FOUNDATIONS OR SLAB-ON-GRADE, THE SUB-GRADE SHALL BE PREPARED AND INSPECTED AS REQUIRED BY THE SPECIFICATIONS.
- EW-6. DO NOT BACKFILL OR FILL SOIL MATERIAL ON SURFACES THAT ARE MUDDY, FROZEN, OR CONTAIN FROST AND/OR ICE.
- EW-7. PLACE BACKFILL AND FILL SOIL MATERIALS EVENLY ON ALL SIDES OF STRUCTURES TO REQUIRED ELEVATIONS AND UNIFORMLY ALONG THE FULL LENGTH OF EACH STRUCTURE.


ABBREVIATIONS

- B.O. = BOTTOM OF _____
BP# = BASE PLATE TYPE
BRG = BEARING
C TO C = CENTER TO CENTER
CCJ = CONSTRUCTION CONTROL JOINT
CJ = CONTROL JOINT
CLSM = CONTROLLED LOW STRENGTH MATERIAL ("FLOWABLE FILL")
CONT = CONTINUOUS
DBLT = DOUBLE TEE
DIA = DIAMETER
DTB = DOUBLE-TEE BEARING
EF = EACH FACE
EL = ELEVATION
EW = EACH WAY
F# = SPREAD FOOTING TYPE
FDTN = FOUNDATION
FV = FIELD VERIFY
GALV = GALVANIZED
HPC = HIGH PERFORMANCE COATING
JB = JOIST BEARING
LLH = LONG LEG HORIZONTAL
LLV = LONG LEG VERTICAL
NIC = NOT IN CONTRACT
NTS = NOT TO SCALE
OC = ON CENTER
P# = PIER TYPE
PCB = PRECAST BEARING (ELEVATION)
PRCST = PRECAST
Rxn = REACTION
SF# = STRIP FOOTING TYPE
SIM = SIMILAR
SST = STAINLESS STEEL
STL = STEEL
T.O. = TOP OF _____
TBD = TO BE DETERMINED
TOC = TOP OF COLUMN
TOF = TOP OF FOOTING
TOL = TOP OF LEDGE
TOP = TOP OF PIER
TOS = TOP OF STEEL
TOW = TOP OF WALL
TPC = TOP OF PRECAST
TSL = TOP OF SLAB
TYP = TYPICAL
UNO = UNLESS NOTED OTHERWISE
WWF = WELDED WIRE FABRIC/REINFORCEMENT


FOUNDATION PLAN



FRAMING PLAN



GENERAL SYMBOLS



TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

M&H NO.: 2013700-1711696.01
DATE: March 22, 2019
DESIGNED BY: FLB
DRAWN BY: MJE
CHECKED BY: JAL
DO NOT SCALE DRAWINGS

SHEET CONTENTS

STRUCTURAL NOTES

SHEET NO.:

S-001

C:\Revit Local\201\3700-171695-01-S-CENTRAL-2019_mrk.elli@meadhunt.com.rvt 3/22/2019 2:51:56 PM

STRUCTURAL STEEL NOTES

- MATERIAL PROPERTIES (U.N.O.)**
W-SHAPES - Fy = 50 KSI (A992 OR A572 Gr 50)
C-SHAPES & ANGLES - Fy = 36 KSI (A36)
PLATES & BARS - Fy = 36 KSI (A36)
RECTANGULAR HSS - Fy = 46 KSI (A500 Gr B)
ROUND HSS - Fy = 42 KSI (A500 Gr B)
PIPE - Fy = 35 KSI (A53 Gr B)
RODS - Fy = 36 KSI (A36)
- S-1. STEEL BEAMS WITH RESIDUAL CAMBER RESULTING FROM MILL FABRICATION OR ROLLING SHALL BE SHOP FABRICATED AND ERECTED SUCH THAT THIS RESIDUAL CAMBER COUNTERACTS GRAVITY LOAD DEFLECTION.
- S-2. ALL BOLTED CONNECTIONS SHALL UTILIZE 3/4 INCH DIAMETER A325 BOLTS TIGHTENED TO THE SNUG-TIGHT CONDITION. THE SNUG-TIGHT CONDITION IS DEFINED BY THE RCSC'S "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS", UNLESS INDICATED OTHERWISE.
- S-3. STEEL CONNECTIONS NOT DETAILED ON THE PLANS ARE TO BE THE FABRICATOR'S STANDARD AND ARE TO BE SELECTED AND DESIGNED IN ACCORDANCE WITH AISC ASD SPECIFICATIONS, TYPE 2 FRAMING CONNECTIONS, FOR THE REACTIONS INDICATED.
- MINIMUM NO. BOLTS PER CONNECTION
n = 2 FOR MEMBERS 10 INCHES DEEP OR LESS
n = 3 FOR MEMBERS 12, 14, OR 15 INCHES DEEP
n = 4 FOR MEMBERS 16 OR 18 INCHES DEEP
n = 5 FOR MEMBERS 21 OR 24 INCHES DEEP
n = 6 FOR MEMBERS 27 OR 30 INCHES DEEP
n = 8 FOR MEMBERS 33 OR 36 INCHES DEEP
- S-4. THE MINIMUM CONNECTION PLATE/ANGLE THICKNESS SHALL BE 5/16", THE MINIMUM WELD 1/4", AND THE MINIMUM DESIGN LOAD ON ANY CONNECTION 10 KIPS, UNLESS INDICATED OTHERWISE.
- S-5. ALL CONNECTIONS TO PIPE AND TUBE COLUMNS SHALL BE THROUGH PLATE CONNECTIONS UNLESS OTHERWISE INDICATED.
- S-6. ALL ANCHOR BOLTS ARE TO BE 3/4" INCH DIAMETER F1554 Gr. 36 THREADED RODS UNLESS INDICATED OTHERWISE. (2)-1/2 INCH DIAMETER ANCHOR BOLTS SHALL BE PROVIDED AT ALL BEAM AND LINTEL BEARINGS ON CONCRETE OR MASONRY, UNLESS INDICATED OTHERWISE.
- S-7. POST INSTALLED ANCHORS ARE TO BE ADHESIVE ANCHORS. INSTALL ANCHORS WITH EMBEDMENT DEPTHS INDICATED, UNLESS INDICATED OTHERWISE.
- S-8. STUD ANCHORS ARE TO BE NELSON STUDS OR EQUAL (ASTM A108).
- S-9. BEAM AND LINTEL PLATES SHALL BE FULLY GROUTED WITH A MINIMUM 1/2" NON-SHRINK GROUT.
- S-10. ALL WELDING OF NEW STEEL IS TO BE WITH E70XX ELECTRODES, U.N.O. WELDING SHALL BE IN ACCORDANCE WITH THE LATEST AWS SPECIFICATIONS BY CERTIFIED WELDERS.
- S-11. WHEN FIELD WELDING TO EXISTING STEEL, ADJUST WELDING PROCEDURES AS REQUIRED TO BE COMPATIBLE WITH THE NEW AND EXISTING STEEL.
- S-12. THE CONTRACTOR SHALL FURNISH AND INSTALL MISCELLANEOUS STEEL (CURBS, HANGERS, BRACING, ETC.) AS INDICATED AND AS NECESSARY PER ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS.
- S-13. ALL EXTERIOR MASONRY SHELF ANGLES, LINTEL BEAMS, AND LINTEL PLATES SHALL BE HOT DIPPED GALVANIZED ACCORDING TO ASTM A123.

COLD FORMED STEEL FRAMING NOTES

- CF-1. COLD FORMED STEEL WORK SHALL CONFORM TO THE 2012 EDITION (INCLUDING ALL APPLICABLE SUPPLEMENTS AND STANDARDS) OF AISI'S "NORTH AMERICAN SPECIFICATION OF FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS"
- CF-2. REFER TO SPECIFICATIONS FOR COLD FORMED METAL FRAMING MATERIAL PROPERTIES AND OTHER GENERAL REQUIREMENTS. COLD FORMED STEEL SHALL BE GALVANIZED G-60 U.N.O.
- CF-3. STUD, TRACK, AND OTHER APPLICABLE ROLLED SHAPES SHALL CONFORM TO THE NOMENCLATURE AND DIMENSIONS SET FORTH BY THE STEEL STUD MANUFACTURER'S ASSOCIATION (SSMA). REFER TO SSMA'S "PRODUCT TECHNICAL INFORMATION" CATALOG AND ICC ER 4943P FOR MINIMUM SECTION PROPERTIES AND DIMENSIONS.
- CF-4. SCREWS FOR ATTACHING COLD FORMED STEEL TO COLD FORMED STEEL SHALL BE CORROSION RESISTANT, SELF DRILLING, SELF TAPPING, #8 OR #10 AS INDICATED, PAN OR HEX HEAD, WITH LENGTH, POINT STYLE AND INSTALLATION METHOD IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS. PROVIDE 3/4" MINIMUM SPACING BETWEEN SCREWS AND 3/4" MINIMUM EDGE DISTANCE U.N.O.
- CF-5. ALL CONNECTIONS SHALL HAVE AT LEAST (2) #8 SCREWS U.N.O.
- CF-6. FASTENERS FROM COLD FORMED STEEL TO STRUCTURAL STEEL OR CONCRETE SHALL BE 0.157" DIAMETER POWDER DRIVEN FASTENERS "SHOT PINS" UNLESS OTHERWISE NOTED. USE HILTI "X-U" FASTENERS WITH 1" EMBEDMENT INTO CONCRETE WITH WASHERS PER MANUFACTURER, U.N.O. SIZE LENGTH OF SHOT PINS AS REQUIRED BY MANUFACTURER'S ICC ES REPORT FOR ATTACHMENT TO STRUCTURAL STEEL. MANUFACTURER'S EDGE DISTANCE AND SPACING REQUIREMENTS SHALL BE MET AND VERIFIED BY THE CONTRACTOR IN THE FIELD.
- CF-7. WALL TRACKS AND ACCESSORIES SHALL BE THE SAME GAUGE AND WIDTH AS THE STUDS, U.N.O.
- CF-8. PROVIDE SUFFICIENT STUDS AND BLOCKING/BACKING AT ALL GRAB BARS AND WALL HUNG EQUIPMENT, MONITORS, CABINETS, TOILET ACCESSORIES, ETC.

METAL DECK

- MATERIAL PROPERTIES (U.N.O.)**
ROOF DECK: GALVANIZED, Fy = 33 KSI
FORM DECK: GALVANIZED, Fy = 33 KSI
- MD-1. SEE PLAN FOR DEPTH AND GAUGE.
- MD-2. METAL DECKING SHALL BE CONTINUOUS OVER 3 SPANS AND HAVE JOINTS OVER SUPPORTING MEMBERS, UNLESS INDICATED OTHERWISE.
- MD-3. BUTTON PUNCHING ROOF DECK IS NOT PERMITTED. REFERENCE DRAWINGS FOR ROOF DECK ATTACHMENT REQUIREMENTS. STRUCTURAL DIAPHRAGM ACTION IS PROVIDED BY THE ROOF DECK AND ITS ATTACHMENT.
- MD-4. ALL MISCELLANEOUS OPENINGS IN METAL ROOF DECK ARE TO BE FRAMED BY L5x3x3/8 ANGLES. LONG LEG OF ANGLES SHALL BE VERTICAL. ANGLES SHALL BE WELDED TO THE TOP CHORD/FLANGE OF ROOF FRAMING AND EACH OTHER, UNLESS INDICATED OTHERWISE.
- MD-4. CONTRACTOR IS RESPONSIBLE FOR PROVIDING POUR STOPS AT EDGES OF METAL DECK PER SDI POUR STOP SELECTION TABLE/RECOMMENDATIONS OR BENT PLATE POUR STOPS AS REQUIRED TO FORM THE SLAB EDGE.

SHEATHING

- SH-1. ROOF DIAPHRAGM SHEATHING:
15/32" APA RATED SHEATHING, EXP. 1, SPAN RATING 40/20. INSTALL WITH LONG DIMENSION OF PANEL PERPENDICULAR TO SUPPORTS. USE 8d NAILS AT 6" O.C. AT ALL SUPPORTED PLYWOOD EDGES, 6" O.C. AT DIAPHRAGM BOUNDARIES, 12" O.C. IN THE FIELD. BLOCK DIAPHRAGMS WHERE INDICATED.
- SH-2. SUBFLOOR/FLOOR DIAPHRAGM SHEATHING:
3/4" T&G APA RATED SHEATHING, EXP. 1, SPAN RATING 48/24. INSTALL WITH LONG DIMENSION OF PANEL PERPENDICULAR TO SUPPORTS. USE 8d NAILS AT 6" O.C. AT ALL SUPPORTED PLYWOOD EDGES, 6" O.C. AT DIAPHRAGM BOUNDARIES, AND 12" O.C. IN THE FIELD. BLOCK DIAPHRAGMS WHERE INDICATED.
- SH-3. SHEAR WALL SHEATHING:
1/2" APA RATED SHEATHING, EXP. 1, SPAN RATING 24/16. INSTALL WITH LONG DIMENSION OF PANEL PARALLEL TO SUPPORTS. USE 8d NAILS AT 4" O.C. AT ALL PANEL EDGES, AND 12" O.C. IN THE FIELD. BLOCK SHEAR WALLS WHERE INDICATED.
- SH-4. WHEN WINDOWS OCCUR WITHIN SHEAR WALLS. NAIL SHEAR PANEL TO DOUBLE STUD TRIMMER AND HEADERS WITH (2) ROWS AT 3" O.C. STAGGERED (SEE SHEAR WALL SCHEDULE FOR NAIL SIZE)

SHOP DRAWINGS

- SD-1. SHOP DRAWINGS SHALL BE SUBMITTED FOR STRUCTURAL ITEMS AS REQUIRED BY THE SPECIFICATIONS. CONSTRUCTION DOCUMENTS SHALL NOT BE REPRODUCED FOR USE AS SHOP DRAWINGS.
- SD-2. THE GENERAL CONTRACTOR SHALL REVIEW ALL SHOP DRAWINGS AND PRODUCT DATA FOR CONFORMANCE WITH THE CONSTRUCTION DOCUMENTS PRIOR TO SUBMITTAL. REVIEWED SUBMITTALS SHALL BE STAMPED BY THE CONTRACTOR. ANY SHOP DRAWING OR PRODUCT DATA NOT REVIEWED AND STAMPED BY THE GENERAL CONTRACTOR WILL BE REJECTED. GENERAL CONTRACTOR SHALL CLOUD OR FLAG ALL ITEMS NOT IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND SHALL VERIFY ALL DIMENSIONS.
- SD-3. ANY CHANGES, SUBSTITUTIONS OR DEVIATIONS FROM THE ORIGINAL CONTRACT DRAWINGS SHALL BE CLOUDED BY THE MANUFACTURER OR FABRICATOR. ANY CHANGES, SUBSTITUTIONS, OR DEVIATIONS WHICH ARE CLOUDED OR FLAGGED BY SUBMITTING PARTIES SHALL NOT BE CONSIDERED APPROVED AFTER THE ENGINEER'S REVIEW, UNLESS SPECIFICALLY NOTED ACCORDINGLY BY THE ENGINEER.
- SD-4. THE APPROVED SHOP DRAWINGS DO NOT REPLACE THE ORIGINAL CONTRACT DRAWINGS. ITEMS OMITTED OR SHOWN INCORRECTLY ARE NOT TO BE CONSIDERED CHANGES TO THE ORIGINAL CONTRACT DRAWINGS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ENSURE THAT ITEMS OMITTED OR SHOWN INCORRECTLY ARE CONSTRUCTED IN ACCORDANCE WITH THE CONTRACT DRAWINGS.
- SD-5. SHOP DRAWING REVIEW IS INTENDED ONLY FOR GENERAL CONFORMANCE TO THE DESIGN CONCEPT AND CONSTRUCTION DOCUMENTS.
- SD-6. SHOP DRAWINGS WILL BE RETURNED FOR RESUBMITTAL IF MAJOR ERRORS ARE FOUND DURING REVIEW.
- SD-7. ALLOW A MINIMUM OF (10) WORKING DAYS FOR REVIEW OF SHOP DRAWINGS BY THE STRUCTURAL ENGINEER.

POST-INSTALLED ANCHORS

- PA-1. POST-INSTALLED ANCHORS BASIS OF DESIGNS UNLESS INDICATED OTHERWISE;
- A. EXPANSION ANCHORS
CONCRETE BASE MATERIAL - HILTI KWIK BOLT-TZ
MASONRY BASE MATERIAL - HILTI KWIK BOLT-3
- B. CONCRETE SREW ANCHORS
CONCRETE BASE MATERIAL - SIMPSON TITEN-HD
MASONRY BASE MATERIAL - SIMPSON TITEN-HD
- C. EPOXY ANCHORS
CONCRETE BASE MATERIAL - HILTI HIT-HY 200-R
MASONRY BASE MATERIAL - HILTI HIT-HY Z70
REBAR - HILTI HIT-RE 500 V3
- D. SLEEVE ANCHORS
MASONRY BASE MATERIAL - HILTI HLC-HX
- E. FLUSH ANCHOR (DROP-IN)
TYPICAL - HILTI HDI
PRECAST - HILTI HDI-P

CARPENTRY

- MATERIAL PROPERTIES (U.N.O.)**
ALL LUMBER TO BE DOUGLAS FIR/SO. PINE OF THE FOLLOWING GRADES. MAXIMUM MOISTURE CONTENT SHALL NOT EXCEED 19%.
- REPETITIVE USE MEMBERS/DIMENSION LUMBER FRAMING
STUDS AND PLATES No. 2
JOISTS AND RAFTERS No. 2
2x4 TO 4x4 INCLUSIVE No. 2
2x6 TO 3x16 INCLUSIVE No. 2
- SINGLE USE MEMBERS/TIMBER FRAMING
BEAMS No. 1
4x No. 1
6x OR LARGER No. 1
POST AND MULLIONS No. 1
4x4 AND SMALLER No. 1
4x6 AND LARGER No. 1
6x6 AND LARGER No. 1
- MISCELLANEOUS LUMBER
BLOCKING, FURRING, ETC. No. 3
- GLUE LAMINATED MEMBERS/ENGINEERED WOOD PRODUCTS
AS SPECIFIED.
- C-1. ALL STRUCTURAL LUMBER SHALL BE GRADED IN ACCORDANCE WITH DOC PS 20 AND WEST COAST LUMBER INSPECTION BUREAU/SOUTHERN PINE INSPECTION BUREAU.
- C-2. ALL WOOD BEARING ON CONCRETE OR MASONRY, IF LESS THAN 4'-0" ABOVE GRADE, SHALL BE PRESERVATIVE PRESSURE TREATED.
- C-3. ALL STRUCTURAL PLYWOOD SHALL BE IN ACCORDANCE WITH DOC PS 1.
- C-4. STRUCTURAL MEMBERS SHALL NOT BE CUT FOR PIPES, ETC. UNLESS SPECIFICALLY NOTED OR DETAILED.
- C-5. 2x SOLID BLOCKING SHALL BE PLACED BETWEEN JOISTS OR RAFTERS AT ALL SUPPORTS.
- C-6. HOLES FOR BOLTS SHALL BE BORED 1/32" TO 1/16" LARGER THAN THE NOMINAL BOLT DIAMETER.
- C-7. ALL BOLTS BEARING ON WOOD SHALL HAVE WASHERS UNDER HEAD AND/OR NUT.
- C-8. ALL BOLTS SHALL BE RETIGHTENED PRIOR TO APPLICATION OF PLYWOOD, PLASTER, ETC.
- C-9. CROSS BRIDGING SHALL BE PROVIDED AT 8'-0" O.C. MAXIMUM FOR ALL JOISTS AND RAFTERS MORE THAN 8" IN DEPTH, U.N.O.. USE 2x4 OR AN APPROVED METAL SWAY BRACE.
- C-10. PROVIDE 1x4 DIAGONAL LET-IN BRACING (AT APPROXIMATELY 45°) EVERY 25'-0" IN ALL STUD WALLS NOT SHEATHED. BRACE SHALL RUN CONTINUOUS FROM TOP PLATE TO SILL PLATE, OR APPROVED METAL SWAY BRACE.
- C-11. ATTACH 2x NAILERS TO STRUCTURAL STEEL WITH 1/2" DIAMETER BOLTS AT 4'-0" O.C., U.N.O.
- C-12. CERTIFICATE OF INSPECTION FOR EACH GLULAM BEAM FROM AN APPROVED TESTING AGENCY TO BE SUBMITTED TO AND APPROVED BY THE BUILDING DEPARTMENT PRIOR TO ERECTION.
- C-13. ALL POSTS SHALL HAVE CONNECTIONS AT TOPS AND BOTTOMS WHICH SHALL BE SIMPSON "CC", "CB", OR "BC HALF BASE" UNLESS SPECIFICALLY DETAILED.
- C-14. USE SIMPSON "CC" OR "ECC" POST CAPS AND "CB" POST BASE FOR ALL POSTS SUPPORTING GLU-LAM BEAMS.
- C-15. ALL CONNECTING HARDWARE, JOIST HANGERS, TIE STRAPS, ETC. SHALL BE SIMPSON "STRONG-TIE" OR EQUIVALENT, UNLESS OTHERWISE NOTED OR DETAILED.
- C-16. ALL NON-BEARING BALLOON FRAMED WALLS EXCEEDING 14'-0" IN HEIGHT AND NOT SUPPORTED BY CEILING JOISTS AT EITHER SIDE SHALL BE FRAMED WITH 2x6 AT 16" O.C. FOR MAXIMUM HEIGHT OF 20'.
- C-17. STUD WALLS SUPPORTING TWO FLOORS AND A ROOF SHALL BE FRAMED WITH 2x6 OR 3x4 STUDS AT 16" O.C.
- C-18. PROVIDE DOUBLE FLOOR JOIST UNDER ALL PARALLEL NON-BEARING PARTITIONS.
- C-19. PROVIDE CONTINUOUS BLOCKING BETWEEN FLOOR JOISTS UNDER ALL BEARING WALLS.
- C-20. CEILING JOISTS SHALL BE 2x6 AT 16" O.C. (MAX. SPAN = 14'-1").
- C-21. USE SIMPSON PC OR EPC ON ALL POST/BEAM/CONNECTIONS UNLESS NOTED ON PLANS.
- C-22. USE SIMPSON U-HANGERS ON ALL JOIST/BEAM OR BEAM/BEAM CONNECTIONS UNLESS NOTED ON PLANS.

DELEGATED DESIGN SUBMITTALS

- DOCUMENTS FOR DELEGATED DESIGN SUBMITTAL ITEMS SHALL BE REVIEWED BY THE ENGINEER OF RECORD IN RESPONSIBLE CHARGE WHO SHALL FORWARD THEM TO THE BUILDING OFFICIAL WITH A NOTATION INDICATING THAT THEY HAVE BEEN REVIEWED AND ARE IN GENERAL CONFORMANCE WITH THE DESIGN OF THE BUILDING.
- DS-1. ANCHORAGE AND BRACING REQUIREMENTS FOR MECHANICAL, HVAC, PLUMBING, PROCESS AND ELECTRICAL EQUIPMENT INCLUDING FLOOR AND ROOF SUPPORTED EQUIPMENT.
- DS-2. METAL STAIRS - SPECIFICATION SECTION 055113 AND 055119.
- DS-3. PIPE AND TUBE RAILINGS - SPECIFICATION SECTION 055213.
- DS-4. PEMB - SPECIFICATION SECTION 133419.

CARPENTRY CONT.

- C-23. NAILING SCHEDULE (U.N.O.)
1. THIS NAILING IS TYPICAL UNLESS OTHERWISE NOTED OR DETAILED.
2. TYPICAL NAILS SHALL BE BOX OR COMMON WIRE NAILS.
3. SPECIFICALLY DETAILED CONNECTIONS SHALL BE COMMON WIRE NAILS.
4. NAILING SCHEDULE:
- JOISTS OR RAFTERS TO SIDES OR STUDS 3 - 16d
8" DEPTH OR LESS 1 - 16d
FOR EACH ADDITIONAL 4" IN DEPTH
- JOISTS OR RAFTERS AT ALL BEARING 3 - 8d
TOE NAILS EACH SIDE
- STUDS TO BEARING 2 - 8d
TOE NAILS EACH SIDE
- BLOCKING BETWEEN JOISTS OR RAFTERS TO JOISTS OR RAFTERS 2 - 10d
TOE NAILS EACH SIDE, EACH END TO JOISTS OR RAFTER BEARING 2 - 10d
TOE NAILS EACH SIDE
- BLOCKING BETWEEN STUDS EACH END - TOE NAILS 2 - 10d
END NAILS 2 - 16d
- PROGRESSIVE BLOCKING 2 - 16d
RAFTER TO BLOCK AND BLOCK TO CONTINUOUS NAILER
- MULTIPLE STUDS 16d AT 24" O.C.
STAGGER FOR STUDS WIDER THAN 4"
- RIBBON TO STUDS 2 - 8d
1x RIBBON 2 - 16d
2x RIBBON
- DOUBLE TOP PLATES 2 - 16d
LOWER PLATE TO TOP OF STUD UPPER TO LOWER PLATE 16d AT 16" O.C.
SPLICE (4'-0" MIN.) EACH SIDE OR BUTT IN TOP PLATE 6 - 16d
UPPER TO LOWER PLATE AT INTERSECTION 3 - 16d
- CEILING STRIPS 1x4 PER BEARING (STRONGHOLD TYPE) 2 - 8d
2x3 PER BEARING (STRONGHOLD TYPE) 1 - 16d
- BUILT-UP BEAMS 20d AT 32" O.C.
TOP AND BOTTOM STAGGERED
- 1x6 LET IN BRACES, EACH BEARING PRE-DRILL HOLES FOR NAILS 2 - 20d AT END
- PLYWOOD NAILING (SEE SHEATHING NOTES)

PRE-ENGINEERED METAL BUILDING NOTES

- MB-1. THE ENTIRE PRE-ENGINEERED METAL BUILDING SYSTEM SHALL BE DESIGNED BY THE METAL BUILDING MANUFACTURER IN CONFORMANCE TO THE INTERNATIONAL BUILDING CODE AND/OR STATE/LOCAL REQUIREMENTS, AND THE "LOW-RISE BUILDING SYSTEMS MANUAL" AS PUBLISHED BY THE METAL BUILDING MANUFACTURER'S ASSOCIATION. WHERE THESE CRITERIA CONFLICT, THE MORE STRINGENT CRITERIA SHALL APPLY.
- MB-2. IT IS THE PRE-ENGINEERED METAL BUILDING MANUFACTURER'S RESPONSIBILITY TO DESIGN THE COMPLETE BUILDING SYSTEM (STEEL FRAMING, ANCHOR BOLTS, PURLINS, GIRTS, BRACING, CONNECTIONS, ROOFING, WALL PANELS, ETC. SUBMIT A CERTIFICATION LETTER BEARING THE SEAL OF A PROFESSIONAL ENGINEER STATING THE BUILDING SYSTEM DESIGN MEETS THE INDICATED CODE, PERFORMANCE, AND LOADING REQUIREMENTS.
- MB-3. THE PRE-ENGINEERED METAL BUILDING MANUFACTURER SHALL BE CERTIFIED BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION CATEGORY MB.
- MB-4. THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF THE ENTIRE METAL BUILDING SYSTEM FOR REVIEW. THE CONTRACTOR SHALL ALSO SUBMIT A COMPLETE STRUCTURAL DESIGN ANALYSIS OF THE BUILDING SYSTEM. THE SHOP DRAWING SUBMITTAL SHALL INCLUDE ATTACHMENT BOLT REQUIREMENTS AND FOUNDATION REACTIONS. ALL SHOP DRAWING AND CALCULATION SUBMITTALS SHALL BEAR THE SEAL OF A PROFESSIONAL ENGINEER.
- MB-5. DESIGN LOADS TO BE USED IN CONNECTION WITH THE METAL BUILDING DESIGN ARE PER THE "DESIGN CRITERIA NOTES". IN ADDITION TO THE ACTUAL DEAD LOAD, AN ADDITIONAL COLLATERAL ROOF FRAMING DEAD LOAD OF 10 PSF SHALL BE INCLUDED. COORDINATE ANY EQUIPMENT LOADS WITH THE MECHANICAL AND ARCHITECTURAL DRAWINGS.
- MB-6. CALCULATIONS FOR FRAME DEFLECTIONS SHALL BE DONE USING ONLY THE BARE FRAME METHOD. REDUCTIONS BASED ON ENGINEERING JUDGEMENT USING THE ASSUMED COMPOSITE STIFFNESS OF THE BUILDING ENVELOPE SHALL NOT BE PERMITTED. DRIFT SHALL FOLLOW AISC'S "SERVICEABILITY DESIGN CONSIDERATIONS FOR LOW-RISE BUILDINGS". CALCULATIONS SHALL BE SUBMITTED VERIFYING THAT THE ACTUAL DRIFT UNDER CODE REQUIRED LOADINGS DOES NOT EXCEED THE ALLOWABLE.
- MB-7. THE PRE-ENGINEERED MANUFACTURER SHALL PROVIDE ALL GIRTS, PURLINS, AND OTHER COMPONENTS REQUIRED FOR A COMPLETE SYSTEM. ALL WALL SYSTEMS, SUCH AS METAL STUDS, STOREFRONTS, ETC. SHALL BE PROPERLY SUPPORTED BY THE METAL BUILDING SYSTEM. ALLOWABLE DEFLECTIONS OF COMPONENTS SHALL BE IN ACCORDANCE WITH THE INTERNATIONAL BUILDING CODE.
- MB-8. THE FOUNDATION DESIGN IS BASED UPON INDUSTRY STANDARDS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF ANY REVISIONS REQUIRED AS A RESULT OF A CHANGE IN THE BUILDING DESIGN ASSUMPTIONS, INCLUDING REDESIGN OF THE FOUNDATIONS.
- MB-9. THE SIZE, NUMBER AND PLACEMENT PATTERN OF ALL ANCHOR BOLTS SHALL BE DETERMINED BY THE PRE-ENGINEERED BUILDING MANUFACTURER. MINIMUM ANCHOR BOLT EMBEDMENTS ARE INDICATED ON THE CONTRACT DRAWINGS.
- MB-10. THE PRE-ENGINEERED METAL BUILDING SHALL BE DESIGNED BY THE MANUFACTURER TO RESIST LATERAL LOADS AS FOLLOWS:
INTERIOR FRAME LINES - RIGID FRAMES (PINNED BASED COLUMNS)
PERIMETER WALL LINES - BRACED BAYS OR PORTAL FRAMES
- MB-11. THE METAL BUILDING ERECTOR SHALL PROVIDE ALL TEMPORARY GUYING AND BRACING (SEE "GENERAL STRUCTURAL NOTES").
- MB-12. UNLESS OTHERWISE NOTED OR SPECIFIED, ALL STEEL MEMBERS SHALL BE CLEANED AND PAINTED IN ACCORDANCE WITH MANUFACTURER'S STANDARD PROCEDURES OR THE CONTRACT DOCUMENTS, WHICHEVER IS MORE STRINGENT.
- MB-13. THE FOUNDATIONS HAVE BEEN DESIGNED FOR THE REACTIONS INDICATED. THESE ARE BASED ON PINNED COLUMN BASES. "FIXED BASE" COLUMNS ARE NOT PERMITTED WITHOUT THE ENGINEER'S WRITTEN APPROVAL.

Mead & Hunt

9595 Core Rd, Suite 510

North Charleston, SC 29406

phone: 843-486-8330

meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT

DISTRICT HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161


ISSUED
03/22/19 SCHEMATIC DESIGN

NOT FOR CONSTRUCTION

M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: FLB
DRAWN BY: MJE
CHECKED BY: JAL
DO NOT SCALE DRAWINGS
SHEET CONTENTS
STRUCTURAL NOTES

SHEET NO.:

S-002



ABBREVIATIONS

∠	ANGLE
@	AT
AB	ANCHOR BOLT
AC	ACOUSTIC
ACC	ACCESS
ACT	ACOUSTIC CEILING TILE
ACP	ACOUSTIC CEILING PANEL
AD	AREA DRAIN
ADD	ADDITIONAL
ADJ	ADJUSTABLE
AFF	ABOVE FINISH FLOOR
AHU	AIR HANDLING UNIT
AL	ALUMINUM
ALT	ALTERNATE
AP	ACCESS PANEL
APPROX	APPROXIMATE
ARCH	ARCHITECTURAL
ASPH	ASPHALT

BB	BOND BEAM
BD	BOARD
BF	BOTH FACES
BFC	BELOW FINISH CEILING
BG	BUMPER GUARD
BIT	BITUMINOUS
BLDG	BUILDING
BLKG	BLOCKING
BLKT	BLANKET
BM	BEAM/BENCH MARK
BLK	BLOCK
BOT	BOTTOM
BRG	BEARING
BRKR	BREAKER
BRK	BRICK
BRKT	BRACKET
BS	BACK SPLASH
BSMT	BASEMENT
BTWN	BETWEEN

CAB	CHANNEL
CER	CERAMIC
CFCI	CONTRACTOR FURNISHED, CONTRATOR INSTALLED
CG	CORNER GUARD
CH	COAT HOOK
CIP	CAST IN PLACE
CJ	CONTROL JOINT/CONSTRUCTION
JOINT	
CLG	CEILING
CLO	CLOSET/CLOSURE
CLR	CLEAR
COL	COLUMN
COMB	COMBINATION
CMU	CONCRETE MASONRY UNIT
CONC	CONCRETE
CONF	CONFERENCE
CONN	CONNECTION/CONNECT
CONST	CONSTRUCTION
CONT	CONTINUOUS
CONTR	CONTRACTOR
CORR	CORRIDOR
CPT	CARPET
CR	COAT RACK/CURTAIN ROD
CSG	CASING
CT	CERAMIC TILE
CTR	CENTER/COUNTER
CTSK	COUNTERSUNK
CUH	CABINET UNIT HEATER
CW	COLD WATER

D	DEPTH
DBL	DOUBLE
DET	DETAIL
DF	DRINKING FOUNTAIN
DIA	DIAMETER
DIAQ	DIAGONAL
DIM	DIMENSION
DIR	DIRECTION
DIV	DIVISION
DM	DEMOUNTABLE PARTITION
DN	DOWN
DO	DITTO
DR	DOOR
DRWR	DRAWER
DS	DOWNSPOUT
DWG	DRAWING
DWL	DOWEL
DWS	DEFORMED WELDED STUD

EA	EACH
EC	ELECTRICAL CONTRACTOR
EF	EACH FACE
EH	ELECTRICAL HEATER/EXHAUST
HOOD	
EJ	EXPANSION JOINT
EL	ELEVATION
ELEC	ELECTRICAL
ELEV	ELEVATOR/ELEVATION
EMBED	EMBEDDED
EMER	EMERGENCY
ENT	ENTRANCE
EQ	EQUAL
EQUIP	EQUIPMENT
ES	EMERGENCY SHOWER
ESR	ELASTOMERIC SHEET ROOFING
ETR	EXISTING TO REMAIN
EVC	ELASTIC VINYL COATING
EW	EACH WAY
EWC	ELECTRIC WATER COOLER
EXC	EXCAVATE
EXP	EXPANSION
EXPD	EXPPOSED
EXPF	EXPLOSION PROOF
EXT	EXTERIOR

FA	FIELD ADJUSTABLE
FV	FIELD VERIFY
FD	FLOOR DRAIN
FDN	FOUNDATION
FE	FIRE EXTINGUISHER
FEC	FIRE EXTINGUISHER CABINET
FHC	FIRE HOSE CABINET
FIN	FINISH
FIX	FIXTURE
FLEX	FLEXIBLE
FLR	FLOOR
FLRG	FLOORING
FP	FIREPROOF/FIRE PROTECTION
FR	FIRE RETARDANT
FS	FULL SIZE/FULL SCALE
FT	FEET
FTG	FOOTING
FURG	FURRING

GA	GAUGE
GAL	GALLON
GALV	GALVANIZED
GB	GRAB BAR
GC	GENERAL CONTRACTOR
GEN	GENERAL
GFCI	GOVERNMENT FURNISHED, CONTRACTOR INSTALLED
GFGI	GOVERNMENT FURNISHED, GOVERNMENT INSTALLED
GFRG	GLASS FIBER REINFORCED CONCRETE
GFRG	GLASS FIBER REINFORCED GYPSUM
GL	GLASS
GMU	GLAZED MASONRY UNIT
GWB	GYPSUM WALL BOARD
GYP	GYPSUM

H	HEIGHT
HDBD	HARDBOARD
HDCP	HANDICAPPED
HDWD	HARDWOOD
HDWE	HARDWARE
HK	HOOK
HM	HOLLOW METAL
HP	HIGH POINT
HR	HANDRAIL
HT	HEIGHT
HVAC	HEATING VENTILATION AND AIR CONDITIONING
HWS	HEAD WELDED STUDS

ID	INSIDE DIAMETER
IMP	INSULATED METAL PANEL
IN	INCHES
INFO	INFORMATION
INSUL	INSULATION
INT	INTERIOR
IPW	INSULATED PLENUM WALL
IRF	INSULATED ROOF FILL

JAN	JANITOR
JS	JANITOR SINK
JST	JOIST
JT	JOINT
KD	KNOCKED DOWN
KO	KNOCK-OUT / KNEE OPENING

L	LENGTH
LAB	LABORATORY
LAM	LAMINATED
LB	POUND
LBS	POUNDS
LD	LINEAR DIFFUSER
LDG	LANDING
LF	LINEAR FOOT
LG	LONG
LGT	LIGHT
LKR	LOCKER
LLH	LONG LEG HORIZONTAL
LLV	LONG LEG VERTICAL
LONG	LONGITUDINAL
LP	LOW POINT
LSH	LONG SLOTTED HOLE
LTG	LIGHTING
LVR	LOUVER
LWC	LIGHTWEIGHT CONCRETE

MACH	MACHINE
MAN	MANUAL
MAR	MARBLE
MAS	MASONRY
MATL	MATERIAL
MAX	MAXIMUM
MB	MACHINE BOLT
MBW	MASONRY BEARING WALL
MC	MECHANICAL CONTRACTOR
MDO	MEDIUM DENSITY OVERLAY
MECH	MECHANICAL
MEMB	MEMBRANE
MET	METAL
MEZZ	MEZZANINE
MFR	MANUFACTURER
MIN	MINIMUM
MIR	MIRROR
MISC	MISCELLANEOUS
MK	MARK
ML	METAL LATH
MLDG	MOLDING
MO	MASONRY OPENING
MP	METAL PARTITION
MS	MACHINE SCREW
MTD	MOUNTED
MTG	MOUNTING

NA	NOT APPLICABLE
NIC	NOT IN CONTRACT
NO	NUMBER
NOM	NOMINAL
NS	NONSHRINK
NIS	NOT TO SCALE
NWC	NORMAL WEIGHT CONCRETE

OA	OVERALL
OC	ON CENTER
OD	OUTSIDE DIAMETER/OVERFLOW DRAIN
OFF	OFFICE
OPNG	OPENING
OPP	OPPOSITE
OZ	OUNCE

PART	PARTITION
PC	PIECE
PCC	PRECAST CONCRETE
PCPL	PORTLAND CEMENT PLASTER
PDWR	PAPER TOWEL DISPENSER & WASTE RECEPTACLE
PEMB	PRE-ENGINEERED METAL BUILDING
PH	PHILLIPS HEAD/PHASE
PL	PLASTIC LAMINATE/PLATE/PROPERTY LINE
PLAS	PLASTER
PLBS	PLUMBING
PLYWD	PLYWOOD
PM	PROTECTED METAL
PNL	PANEL
PNLG	PANELING
POL	POLISHED
PR	PAIR
PRE FAB	PREFABRICATED
PRE FIN	PRE-FINISHED
PSF	POUNDS PER SQUARE FOOT
PSI	POUNDS PER SQUARE INCH
PT	POINT/PAINT
PTM	PAINT TO MATCH
PVC	POLYVINYL CHLORIDE

QT	QUARRY TILE
QTY	QUANTITY

RAD	RADIUS
RAH	ROOFTOP AIR HANDLING UNIT
RB	RUBBER BASE
RC	REINFORCED CONCRETE
RCP	RADIANT CEILING PANEL
	/ REFLECTED CEILING PLAN
RD	ROOF DRAIN
REC	RECESSED
REF	REFERENCE
REINF	REINFORCING
REL	RELOCATE
REM	REMAINDER
REQD	REQUIRED
RES	RESILIENT
RET	RETURN
RI	ROUGH IN
RM	ROOM
RO	ROUGH OPENING
RT	RUBBER TILE
RUB	RUBBER

SAT	STANDARD AGGREGATE TOPPING
SB	SOIL BEARING
SC	SEAMLESS COATING
SCF	SPECIAL CONCRETE FINISH
SCHD	SCHEDULE
SD	SOAP DISPENSER
SE	SHELF EDGE
SECT	SECTION
SF	SAND FLOAT
SG	SUPPLY AIR GRILLE
SGL	SINGLE
SH	SHELF
SHD	SHOWER DOOR
SHT	SHEET
SIM	SIMILAR
SJ	STEEL JOIST
SLV	SHORT LEG VERTICAL
SM	SMOOTH
SND	SANITARY NAPKIN DISPENSER
SNV	SANITARY NAPKIN VENDER
SOG	SLAB ON GRADE
SPEC	SPECIFICATION
SPR	SPRINKLER
SQ	SQUARE
SR	SHOWER ROD
SS	STAINLESS STEEL
ST	STREET
STD	STANDARD
STL	STEEL
STO	STORAGE
STRU	STRUCTURAL/STRUCTURE
SUSP	SUSPENDED
SV	SHEET VINYL
SYM	SYMMETRICAL

ABBREVIATIONS ABOVE ARE FOR ARCHITECTURAL SHEETS ONLY.

HATCH SYMBOLS

	EARTHWORK		PLYWOOD
	GRAVEL		FINISH LUMBER
	PLASTER, SAND, GROUT		WOOD STUDS, BLOCKING
	CONCRETE		STEEL STUDS
	CONCRETE MASONRY		GYPSUM WALLBOARD
	CLAY MASONRY		ACOUSTICAL TILE
	PRECAST CONCRETE		BATT INSULATION
	METAL		RIGID INSULATION

LEGEND - PLAN SYMBOLS

	BUILDING SECTION SYMBOL
	WALL SECTION SYMBOL
	DETAIL SYMBOL
	ENLARGED PLAN SYMBOL
	EXTERIOR ELEVATION SYMBOL
	INTERIOR ELEVATION SYMBOL
	KEYED NOTE IDENTIFICATION
ROOM NAME 	ROOM NAME AND NUMBER
	WALL TYPE IDENTIFICATION
	WINDOW IDENTIFICATION
	DOOR IDENTIFICATION
	1 HOUR FIRE RATED WALL
	FIRE EXTINGUISHER - SURFACE MOUNT
	FIRE EXTINGUISHER CABINET AND FIRE EXTINGUISHER - SEMI- RECESSED
	FLOOR DRAIN
	EXISTING GRID LINES
	NEW GRID LINES
	LEVEL OR SPOT ELEVATIONS
	CEILING HEIGHT & FINISH

Mead
& Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall
not be duplicated, disclosed, or used on any
other project or extension of this project,
except by written agreement with Mead &
Hunt, Inc. Mead & Hunt shall not be
responsible for any unauthorized use of, or
alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN


NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS
SHEET CONTENTS
NOTES & SYMBOLS

SHEET NO.:

A-001



ARCHITECTURAL PLAN GENERAL NOTES:

- SITE DATUM OF FINISHED FIRST FLOOR INDICATED ON CIVIL SITE PLAN = ELEVATION 100'-0" ON STRUCTURAL DRAWINGS.
- FIELD VERIFY ALL DIMENSIONS, BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR FINAL DECISION.
- PRE-ENGINEERED METAL BUILDING MANUFACTURER IS RESPONSIBLE FOR ALL ADDITIONAL STRUCTURE REQUIRED FOR BUILDING MOUNTED AND SUPPORTED EQUIPMENT AND COMPONENTS ATTACHED, ANCHORED OR CONNECTED TO THE PEMB. RESPONSIBILITY INCLUDES LOCATION OF PEMB BRACING TO NOT INTERFERE WITH THE USE AND LOCATION SHOWN OF DOORS, EQUIPMENT, ETC.
- SLOPE ALL EXTERIOR CONCRETE SURFACES AWAY FROM BUILDING AT 1/8" PER FOOT, UNLESS NOTED OTHERWISE. WHERE ADJACENT TO BUILDING, FINAL GRADE SHOULD BE MINIMUM 6" BELOW TOP OF SLAB UNLESS NOTED OTHERWISE.
- SEE STRUCTURAL DRAWING S-111 FOR CONTROL JOINTS IN CONCRETE SLAB.
- ALL EXTERIOR DIMNSIONS ARE TO THE EXTERIOR FACE OF GIRT, UNLESS NOTED OTHERWISE.

KEYED NOTES

- 4.103 PRE-FINISHED 3" X 4" METAL DOWNSPOUT BY PEMB MANUFACTURER. CONNECT TO STORM. COLOR TO MATCH METAL ROOF.
- 4.105 TIMBER CANOPY COLUMN
- 4.106 PLASTIC LAMINATE BASE CABINETS W/ SOLID SURFACE COUNTERS
- 4.107 STAINLESS STEEL PASS THROUGH WINDOW W/ SOLID SURFACE COUNTER
- 4.108 STAINLESS STEEL HI-LO DRINKING FOUNTAIN
- 4.111 PIPE BOLLARD, PAINT SAFETY YELLOW
- 4.114 PROVIDE HEAVY-DUTY TRENCH DRAIN FULL LENGTH OF SECTIONAL DOOR. SLOPE SLAB TO DRAIN.
- 4.116 ALUMINUM LOUVER FRAME SCREEN WALL W/ WOOD GRAIN FINISH.
- 4.403 INFRARED HEATER


TOILET ROOM/CASEWORK GENERAL NOTES:

- LAVATORIES IN TOILET ROOM ARE SOLID SURFACE COUNTERTOPS WITH UNDERCOUNTER MOUNTED BOWLS, BACKSPLASH SHALL BE INTEGRAL WITH COUNTERTOP.
- PROVIDE BLOCKING IN WALLS FOR ALL WALL MOUNTED ACCESSORIES.
- ALL DOORS AND DRAWERS IN CASEWORK TO HAVE LOCKS AND KEYS.
- ALL EXPOSED SURFACES OF MILLWORK TO BE P. LAMINATE ON 3/4" PART. BD., TYPICAL, UNLESS NOTED OTHERWISE.
- PROVIDE WATER RESISTANT GYPSUM WALLBOARD AT ALL WET AREAS AND/OR AREAS TO RECEIVE WALL TILE.
- RESTROOMS SHALL RECEIVE THE FOLLOWING ACCESSORIES. FINISH SHALL STAINLESS STEEL UNLESS NOTED OTHERWISE:
 - WALL MOUNTED LIQUID SOAP DISPENSER - QTY: 1 PER RESTROOM
 - SEMI-RECESSED PAPER TOWEL DISPENSER/DISPOSAL - QTY: 2 PER RESTROOM
 - ELECTRIC HAND DRYER, BATTERY OPERATED - QTY: 2 PER RESTROOM
 - RECESSED BABY CHANGING STATION - QTY: 1 PER RESTROOM
 - DUAL-ROLL PAPER TOWEL DISPENSER - QTY: 1 PER TOILET
 - TOILET SEAT COVER DISPENSER - QTY: 1 PER TOILET
 - ADA GRAB BARS - QTY: 1 SET OF 3 PER RESTROOM
 - SANITARY NAPKIN VENDOR - QTY: 1 IN WOMEN'S RESTROOM
 - SANITARY NAPKIN DISPOSAL - QTY: 1 PER TOILET IN WOMEN'S RESTROOM
- ALL TOILET PARTITIONS AND URINAL SCREENS SHALL BE STAINLESS STEEL, TOILET PARTITIONS SHALL BE FLOOR MOUNTED.

TRUE PLAN
NORTH NORTH
1
1/8" = 1'-0"

SIGNAGE NOTES:

- PROVIDE 1 ABS ROOM IDENTIFICATION SIGN PER INTERIOR DOOR WITH ROOM NAMES AND NUMBERS MATCHING THOSE IDENTIFIED ON FLOOR PLANS, MOUNT WITH DOUBLE BACKED FOAM MOUNTING TAPE. PROVIDE ADA COMPLIANT BRAILLE.
- PROVIDE ADA COMPLIANT ABS RESTROOM SIGNS, 1 PER RESTROOM.




TRUE PLAN
NORTH NORTH
1 MEZZANINE PLAN
1/8" = 1'-0"

ARCHITECTURAL PLAN GENERAL
NOTES:

1. SITE DATUM OF FINISHED FIRST FLOOR INDICATED ON CIVIL SITE PLAN = ELEVATION 100'-0" ON STRUCTURAL DRAWINGS.
2. FIELD VERIFY ALL DIMENSIONS. BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR FINAL DECISION.
3. PRE-ENGINEERED METAL BUILDING MAUFACTURER IS RESPONSIBLE FOR ALL ADDITIONAL STRUCTURE REQUIRED FOR BUILDING MOUNTED AND SUPPORTED EQUIPMENT AND COMPONENTS ATTACHED, ANCHORED OR CONNECTED TO THE PEMB. RESPONSIBILITY INCLUDES LOCATION OF PEMB BRACING TO NOT INTERFERE WITH THE USE AND LOCATION SHOWN OF DOORS, EQUIPMENT, ETC.
4. SLOPE ALL EXTERIOR CONCRETE SURFACES AWAY FROM BUILDING AT 1/8" PER FOOT, UNLESS NOTED OTHERWISE. WHERE ADJACENT TO BUILDING, FINAL GRADE SHOULD BE MINIMUM 6" BELOW TOP OF SLAB UNLESS NOTED OTHERWISE.
5. SEE STRUCTURAL DRAWING S-111 FOR CONTROL JOINTS IN CONCRETE SLAB.
6. ALL EXTERIOR DIMNSIONS ARE TO THE EXTERIOR FACE OF GIRT, UNLESS NOTED OTHERWISE.

KEYED NOTES

- 4.109 REMOVABLE METAL GUARDRAIL
- 4.110 FUTURE FLOOR OPENING FOR STAIR AND ELEVATOR. PROVIDE MEZZANINE FRAMING FOR FUTURE SLAB CUTOUT. DIMENSIONS SHOWN FOR ELEVATOR SHAFT OPENING ARE SIZED TO ACCOMMODATE MOST LOW-RISE MACHINE ROOMLESS TRACTION ELEVATORS. FINAL SIZE SHALL BE CONFIRMED WITH OWNER AND TENANT.




TRUE PLAN
NORTH NORTH
1 ROOF PLAN
1/8" = 1'-0"

ROOF PLAN GENERAL NOTES:

- ALL PRODUCTS LISTED ARE FOR BASIS OF DESIGN INTENT ONLY. APPROVED EQUAL PRODUCTS MAY BE SUBSTITUTED.

KEYED NOTES

- 4.101 PRE-FINISHED INSULATED STANDING SEAM METAL ROOF BY PEMB MANUFACTURER. BASIS OF DESIGN - KINGSPAN KINGZIP 1000 SERIES
- 4.102 PRE-FINISHED 5" X 5" METAL GUTTER BY PEMB MANUFACTURER. COLOR TO MATCH METAL ROOF.
- 4.103 PRE-FINISHED 3" X 4" METAL DOWNSPOUT BY PEMB MANUFACTURER. CONNECT TO STORM. COLOR TO MATCH METAL ROOF.
- 4.104 METAL CANOPY BELOW
- 4.112 SNOW RAIL (FENCE) RETENTION SYSTEM TO BE DESIGNED BY PEMB MANUFACTURER AND INSTALLED BY PEMB CONTRACTOR. LAYOUT SHOWN ON ROOF PLAN IS FOR INTENT ONLY. PEMB MANUFACTURER TO PROVIDED FINAL ENGINEERED LAYOUT. ONLY SNOW RAIL SYSTEM MOUNTED TO VERTICAL RIB AT ROOF PANEL EDGES IS PERMITTED. SNOW GUARDS MOUNTED TO FACE OF PANELS ARE NOT ACCEPTABLE. COLOR TO MATCH ROOF PANELS.



CEILING LEGEND:

	2' x 2' SUSPENDED CEILING GRID		CEILING RECEPTACLES
	GYPSUM BOARD CEILING/ PORTLAND CEMENT PLASTER (PAINTED)		CEILING OCCUPANCY SENSOR
	LIGHT FIXTURE (RECESSED MOUNTED)		CEILING FIRE ALARM DEVICES
	LIGHT FIXTURE (RECESSED MOUNTED 4\"/>		CEILING MASS NOTIFICATION DEVICE
	LIGHT FIXTURE (RECESSED MOUNTED)		CEILING SPEAKER
	LIGHT FIXTURE (RECESSED CAN)		CEILING SECURITY STRODE
	LIGHT FIXTURE (SURFACE MOUNTED)		CEILING CAMERA
	LIGHT FIXTURE (SURFACE MOUNTED)		SPRINKLER HEADS
	LIGHT FIXTURE (SUSPENDED)		SUPPLY AIR DIFFUSER
	LIGHT FIXTURE (SUSPENDED)		RETURN AIR DIFFUSER / EXHAUST GRILL
			EXHAUST FAN

SEE ELECTRICAL FOR
EXACT FIXTURE MODEL

KEYED NOTES

4.401 SUSPENDED METAL CANOPY W/ WOOD WOOD GRAIN FINISH ALUMINUM SOFFIT

CEILING
PLAN GENERAL NOTES:











- SEE ROOM FINISH SCHEDULE FOR FLOOR, WALL AND CEILING FINISHES.
- FIELD VERIFY ALL DIMENSIONS. BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT FOR FINAL DECISION.
- ALL RECESSED LIGHTS, SPRINKLERS, FIRE DETECTION EQUIPMENT, OCCUPANCY SENSORS, ETC. SHALL BE CENTERED IN THE TILES UNLESS NOTED OTHERWISE.
- CENTER ALL CEILING GRIDS IN SPACE UNLESS NOTED OTHERWISE.
- ALL METAL LINEAR DIFFUSERS SHALL BE PAINTED TO MATCH SURROUNDING WALL OR CEILING SURFACE.














REFLECTED CEILING PLAN
1/8" = 1'-0"

3/22/2019 9:00:47 AM C:\Revit Local\2013700-171696.01-A-CENTRAL-2019_marc.godzina.rvt

CEILING LEGEND:

- | | |
|---|--|
|  | 2' x 2' SUSPENDED CEILING GRID |
|  | GYPSUM BOARD CEILING/
PORTLAND CEMENT PLASTER (PAINTED) |
|  | LIGHT FIXTURE (RECESSED MOUNTED) |
|  | LIGHT FIXTURE (RECESSED MOUNTED 4" WIDE OR LESS) |
|  | LIGHT FIXTURE (RECESSED MOUNTED) |
|  | LIGHT FIXTURE (RECESSED CAN) |
|  | LIGHT FIXTURE (SURFACE MOUNTED) |
|  | LIGHT FIXTURE (SURFACE MOUNTED) |
|  | LIGHT FIXTURE (SUSPENDED) |
|  | LIGHT FIXTURE (SUSPENDED) |

- | | |
|---|-------------------------------------|
|  | CEILING RECEPTACLES |
|  | CEILING OCCUPANCY SENSOR |
|  | CEILING FIRE ALARM DEVICES |
|  | CEILING MASS NOTIFICATION DEVICE |
|  | CEILING SPEAKER |
|  | CEILING SECURITY STROBE |
|  | CEILING CAMERA |
|  | SPRINKLER HEADS |
|  | SUPPLY AIR DIFFUSER |
|  | RETURN AIR DIFFUSER / EXHAUST GRILL |
|  | EXHAUST FAN |


SEE ELECTRICAL FOR
EXACT FIXTURE MODEL

KEYED NOTES

- 4.402 12 FOOT DIAMETER DESTRATIFICATION FAN
- 4.403 INFRARED HEATER

CEILING
PLAN GENERAL NOTES:

- SEE ROOM FINISH SCHEDULE FOR FLOOR, WALL AND CEILING FINISHES.
- FIELD VERIFY ALL DIMENSIONS. BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT FOR FINAL DECISION.
- ALL RECESSED LIGHTS, SPRINKLERS, FIRE DETECTION EQUIPMENT, OCCUPANCY SENSORS, ETC. SHALL BE CENTERED IN THE TILES UNLESS NOTED OTHERWISE.
- CENTER ALL CEILING GRIDS IN SPACE UNLESS NOTED OTHERWISE.
- ALL METAL LINEAR DIFFUSERS SHALL BE PAINTED TO MATCH SURROUNDING WALL OR CEILING CURFACE.



Mead
& Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall
not be duplicated, disclosed, or used on any
other project or extension of this project,
except by written agreement with Mead &
Hunt, Inc. Mead & Hunt shall not be
responsible for any unauthorized use of, or
alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED

03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LDR
CHECKED BY: RJM

DO NOT SCALE DRAWINGS


SHEET CONTENTS
HANGAR
REFLECTED CEILING
PLAN

SHEET NO.:


A-122

PARTITION GENERAL NOTES:


- PARTITIONS SHALL BE TYPE "SA3" UNLESS OTHERWISE NOTED.
- ALL ELEMENTS OF ACOUSTIC PARTITIONS SHALL EXTEND TO ROOF OR FLOOR DECK ABOVE AND ALL JOINTS AND PENETRATIONS OF ACOUSTIC RATED PARTITIONS SHALL BE FILLED AND SEALED.
- REFER TO "INTERIOR PARTITION TYPE MODIFIERS" FOR SYMBOLS USED TO IDENTIFY ADDITIONAL REQUIREMENTS OR MODIFICATIONS TO BASIC PARTITION TYPES.
- PARTITION TYPES DESCRIBE GENERAL REQUIREMENTS FOR PARTITIONS. REFER TO PRODUCT MANUFACTURERS' SPECIFICATIONS AND REQUIREMENTS FOR APPLICABLE TESTING AGENCIES FOR SPECIFICS OF PARTITION CONSTRUCTION.
- PARTITION REQUIREMENTS SHOWN ARE CONSIDERED MINIMUM STANDARDS. WHERE CONDITIONS OF THE WORK CAUSE PARTITION(S) TO EXCEED LIMITS RECOMMENDED BY MANUFACTURER, REINFORCE PARTITION(S).
- PENETRATIONS IN RATED PARTITIONS AND CONNECTIONS OF THE PARTITIONS TO OTHER PORTIONS OF THE WORK SHALL BE IN ACCORDANCE WITH MANUFACTURERS' RECOMMENDED DETAILS AND IN COMPLIANCE WITH APPLICABLE TESTING AGENCY REQUIREMENTS.
- WHERE A CLEAR DIMENSION OR OPENING IS REQUIRED OR NOTED, MEASURE DIMENSION TO FACE OF PARTITION FINISH.
- REFER TO STRUCTURAL DRAWINGS FOR EXTENT AND DESCRIPTION OF INTERIOR STRUCTURAL WALLS NOT IDENTIFIED BY PARTITION TYPES.
- INSTALL BLOCKING OR BACKER MATERIAL FOR ATTACHMENT/MOUNTING OF WALL HUNG ITEMS OR EQUIPMENT DESCRIBED IN THE DOCUMENTS.
- PROVIDE 5/8" TYPE "X" GYPSUM BOARD (UNLESS NOTED OTHERWISE)
- PROVIDE WATER RESISTANT TYPE GYPSUM BOARD AT AREAS THAT ARE SCHEDULED TO RECEIVE CERAMIC TILE FINISH AND AT AREAS SO REQUIRED BY CODE TO RECEIVE IT.
- PROVIDE TILE BACKER BOARD AT SHOWER AREAS AND AT OTHER WET AREAS THAT ARE SCHEDULED IN ROOM FINISH SCHEDULE TO RECEIVE CERAMIC TILE FINISH.
- INSTALLATION OF GYPSUM BOARD, BACKER BOARD AND BASE BOARD SHALL CONFORM TO REQUIREMENTS FOR FIRE RATINGS AND ACOUSTICAL RATINGS.
- TYPICAL FLOOR PLAN DIMENSIONS OF PARTITIONS ARE TO THE FACE OF METAL STUD UNLESS NOTED OTHERWISE.
- WHERE PARTITIONS AND/OR FURRING MEET, MAINTAIN A FLUSH SURFACE ON THE SIDE WHERE THE FINISH IS STRAIGHT OR CONTINUOUS UNLESS OTHERWISE NOTED.



7 GYP WALL BASE
3" = 1'-0"





8 PARTITION HEAD
3" = 1'-0"




9 PARTITION HEAD
3" = 1'-0"


PARTITION TYPE SYMBOL AND SUBSCRIPT DEFINITIONS:



5 VERTICAL METAL PANEL ON PEMB
3" = 1'-0"




6 ROOF ASSEMBLY
3" = 1'-0"




"MA" SERIES

PTN TYPE	CMU WIDTH	WALL WIDTH	NOTES
MA8	7 5/8"	8"	



"SA" SERIES


PTN TYPE	STUD WIDTH	WALL WIDTH	NOTES
SA3	3 5/8"	4 7/8"	




"FA" SERIES

PTN TYPE	STUD WIDTH	WALL WIDTH	NOTES
FA78	7/8"	1 1/2"	HAT CHANNEL
FA15	1 1/2"	2 1/8"	HAT CHANNEL


10 PARTITION TYPES
1" = 1'-0"




1 STONE ON PEMB
3" = 1'-0"



2 STONE ON CMU
3" = 1'-0"



3 HORIZONTAL METAL PANEL ON PEMB
3" = 1'-0"



4 HANGAR BLDG HORIZONTAL METAL PANEL ON CMU
3" = 1'-0"

BASIS OF DESIGN NOTES:

- ALL PRODUCTS LISTED ARE FOR BASIS OF DESIGN INTENT ONLY. APPROVED EQUAL PRODUCTS MAY BE SUBSTITUTED.

Mead & Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM
DO NOT SCALE DRAWINGS

SHEET CONTENTS
EXTERIOR ASSEMBLIES & PARTITION TYPES

SHEET NO.:

A-141

TRUCKEE TAHOE AIRPORT

DISTRICT
HANGAR 210356 Truckee Airport Rd
Truckee, CA 96161

ISSUED

03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION


M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS

SHEET CONTENTS
EXTERIOR
ELEVATIONS

SHEET NO.:

A-201





KEYED NOTES

- 4.102 PRE-FINISHED 5" X 5" METAL GUTTER BY PEMB MANUFACTURER. COLOR TO MATCH METAL ROOF.
- 4.103 PRE-FINISHED 3" X 4" METAL DOWNSPOUT BY PEMB MANUFACTURER. CONNECT TO STORM. COLOR TO MATCH METAL ROOF.
- 4.112 SNOW RAIL (FENCE) RETENTION SYSTEM TO BE DESIGNED BY PEMB MANUFACTURER AND INSTALLED BY PEMB CONTRACTOR. LAYOUT SHOWN ON ROOF PLAN IS FOR INTENT ONLY. PEMB MANUFACTURER TO PROVIDED FINAL ENGINEERED LAYOUT. ONLY SNOW RAIL SYSTEM MOUNTED TO VERTICAL RIB AT ROOF PANEL EDGES IS PERMITTED. SNOW GUARDS MOUNTED TO FACE OF PANELS ARE NOT ACCEPTABLE. COLOR TO MATCH ROOF PANELS.
- 4.201 MP-1 PRE-FINISHED METAL WALL PANEL BY PEMB MANUFACTURER, BASIS OF DESIGN: MORIN INTEGRITY X-16. COLOR REDWOOD.
- 4.202 MP-2 PRE-FINISHED METAL WALL PANEL BY PEMB MANUFACTURER, BASIS OF DESIGN: MORIN INTEGRITY S-16. COLOR PATINA GREEN.
- 4.203 ADHERED STONE VENEER, BASIS OF DESIGN: ELDORADO STONE, MOUNTAIN LEDGE. MESA VERDE.
- 4.204 ADHERED STONE SILL, BASIS OF DESIGN: ELDORADO STONE, SNAPPED EDGE WAINSCOT SILL. COLOR SAND.
- 4.205 INSULATED ALUMINUM STOREFRONT
- 4.206 INSULATED STANDING SEAM METAL ROOF BY PEMB MANUFACTURER, BASIS OF DESIGN KINGZIP 1000 SERIES
- 4.207 PRE-FINISHED METAL TRIM. COLOR TO MATCH ROOFING.
- 4.208 TIMBER COLUMN / CANOPY SUPPORT
- 4.209 SUSPENDED METAL CANOPY W/ WOOD SOFFIT
- 4.210 BI-FOLDING METAL HANGAR DOOR. INSULATION AND PRE-FINISHED METAL WALL PANEL CLADDING AT INTERIOR AND EXTERIOR BY PEMB MANUFACTURER.
- 4.212 INSULATED ALUMINUM CURTAIN WALL
- 4.213 TIMBER FRAMED CANOPY W/ WOOD SOFFIT
- 4.214 ALUMINUM LOUVER FENCE SCREEN W/ WOOD GRAIN FINISH. WALL BASE TO BE ADHERED STONE VENEER ON CONCRETE OR CMU.

BASIS OF DESIGN NOTES:

1. ALL PRODUCTS LISTED ARE FOR BASIS OF DESIGN INTENT ONLY. APPROVED EQUAL PRODUCTS MAY BE SUBSTITUTED.






1 NORTH ELEVATION
1/8" = 1'-0"

KEYED NOTES

- 4.102 PRE-FINISHED 5" X 5" METAL GUTTER BY PEMB MANUFACTURER. COLOR TO MATCH METAL ROOF.
- 4.103 PRE-FINISHED 3" X 4" METAL DOWNSPOUT BY PEMB MANUFACTURER. CONNECT TO STORM. COLOR TO MATCH METAL ROOF.
- 4.112 SNOW RAIL (FENCE) RETENTION SYSTEM TO BE DESIGNED BY PEMB MANUFACTURER AND INSTALLED BY PEMB CONTRACTOR. LAYOUT SHOWN ON ROOF PLAN IS FOR INTENT ONLY. PEMB MANUFACTURER TO PROVIDED FINAL ENGINEERED LAYOUT. ONLY SNOW RAIL SYSTEM MOUNTED TO VERTICAL RIB AT ROOF PANEL EDGES IS PERMITTED. SNOW GUARDS MOUNTED TO FACE OF PANELS ARE NOT ACCEPTABLE. COLOR TO MATCH ROOF PANELS.
- 4.201 MP-1 PRE-FINISHED METAL WALL PANEL BY PEMB MANUFACTURER, BASIS OF DESIGN: MORIN INTEGRITY X-16. COLOR REDWOOD.
- 4.202 MP-2 PRE-FINISHED METAL WALL PANEL BY PEMB MANUFACTURER, BASIS OF DESIGN: MORIN INTEGRITY S-16. COLOR PATINA GREEN.
- 4.203 ADHERED STONE VENEER, BASIS OF DESIGN: ELDORADO STONE, MOUNTAIN LEDGE, MESA VERDE.
- 4.204 ADHERED STONE SILL, BASIS OF DESIGN: ELDORADO STONE, SNAPPED EDGE WAINSCOT SILL. COLOR SAND.
- 4.205 INSULATED ALUMINUM STOREFRONT
- 4.206 INSULATED STANDING SEAM METAL ROOF BY PEMB MANUFACTURER, BASIS OF DESIGN KINGZIP 1000 SERIES
- 4.207 PRE-FINISHED METAL TRIM. COLOR TO MATCH ROOFING.
- 4.209 SUSPENDED METAL CANOPY W/ WOOD SOFFIT
- 4.210 BI-FOLDING METAL HANGAR DOOR. INSULATION AND PRE-FINISHED METAL WALL PANEL CLADDING AT INTERIOR AND EXTERIOR BY PEMB MANUFACTURER.
- 4.211 FULLY GLAZED VERTICAL LIFT SECTIONAL DOOR
- 4.212 INSULATED ALUMINUM CURTAIN WALL
- 4.215 WOOD GRAIN FINISH ALUMINUM SIDING

BASIS OF DESIGN NOTES:

1. ALL PRODUCTS LISTED ARE FOR BASIS OF DESIGN INTENT ONLY. APPROVED EQUAL PRODUCTS MAY BE SUBSTITUTED.



2 EAST ELEVATION
1/8" = 1'-0"

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS

SHEET CONTENTS
EXTERIOR 3D
REPRESENTATIONS

SHEET NO.:

A-203



3 3D VIEW 3




1 3D VIEW 1




4 3D VIEW 4




2 3D VIEW 2




1 HANGAR - LONGITUDINAL SECTION
1/8" = 1'-0"




3 OFFICE - LONGITUDINAL SECTION
1/8" = 1'-0"



3 OFFICE CROSS SECTION
1/8" = 1'-0"



1 HANGAR - CROSS SECTION
1/8" = 1'-0"



2 HANGAR - CROSS SECTION @ MEZZ.
1/8" = 1'-0"

**Mead
& Hunt**

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall
not be duplicated, disclosed, or used on any
other project or extension of this project,
except by written agreement with Mead &
Hunt, Inc. Mead & Hunt shall not be
responsible for any unauthorized use of, or
alteration to these documents.

**TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2**

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED

03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: MKG
CHECKED BY: RJM


DO NOT SCALE DRAWINGS

SHEET CONTENTS
BUILDING SECTIONS


SHEET NO.:

A-302


3/22/2019 9:01:44 AM C:\Revit Local\2013700-171696.01-A-CENTRAL-2019.marc.godzina.rvt




4 HANGAR - SIDE WALL SECTION 2
1/2" = 1'-0"



3 HANGAR - SIDE WALL SECTION 1
1/2" = 1'-0"



2 HANGAR - BACK WALL SECTION
1/2" = 1'-0"



1 HANGAR DOOR SECTION
1/2" = 1'-0"

Mead
& Hunt

Mead & Hunt, Inc.
5955 Core Rd, Suite 510
North Charleston, SC 29406
phone: 843-486-8330
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall
not be duplicated, disclosed, or used on any
other project or extension of this project,
except by written agreement with Mead &
Hunt, Inc. Mead & Hunt shall not be
responsible for any unauthorized use of, or
alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM
DO NOT SCALE DRAWINGS

SHEET CONTENTS
WALL SECTIONS

SHEET NO.:

A-311

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MKG
DRAWN BY: LD
CHECKED BY: RJM

DO NOT SCALE DRAWINGS


SHEET CONTENTS
WALL SECTIONS

SHEET NO.:


A-312

KEYED NOTES


- 4.102 PRE-FINISHED METAL GUTTER BY PEMB MANUFACTURER. COLOR TO MATCH METAL ROOF.
4.209 SUSPENDED METAL CANOPY W/ WOOD SOFFIT




4 OFFICE - NORTH WALL
1/2" = 1'-0"



3 OFFICE - SECTION AT DORMER
1/2" = 1'-0"



2 OFFICE - END WALL SECTION
1/2" = 1'-0"




1 OFFICE - SOUTH VESTIBULE
1/2" = 1'-0"

DOOR AND HARDWARE SCHEDULE

DOOR NUMBER	DOOR							FRAME						MISCELLANEOUS			REMARKS
	LEAF SIZE			TYPE	MAT'L	GLAZING TYPE	FINISH	TYPE	MAT'L	DETAILS			FINISH	LABEL	HDWR SET	LINTEL	
	QTY.	WIDTH	HEIGHT							HEAD	JAMB	OTHER					
101A	-	70'-0"	22'-0"	BF													BI-FOLDING HANGAR DOOR. EXTERIOR TO RECEIVE MP-1, INTERIOR TO RECEIVE LINER PANELS
101B	(1)	2'-10 1/4"	7'-1 1/8"	MS	AL	IN, T											
101C	(2) *	5'-10 1/4"	7'-1 1/8"	MS	AL	IN, T											
101D	(2)	3'-0"	7'-0"	FG	AL	T								45 MIN.			
101E	(2) *	5'-9"	7'-1 1/8"	MS	AL	IN, T											
101F	-	18'-0"	12'-0"	SC2	STL												
101G	(1)	2'-10 1/4"	7'-1 1/8"	MS	AL	IN, T											
101H	-	3'-0"	3'-0"	FC	STL												
102A	(2)	3'-0"	7'-0"	MS	AL	IN, T											
102B	(2)	3'-0"	7'-0"	MS	AL	IN, T											
103	(1)	3'-0"	7'-0"	FG	HM	T											
104	(1)	3'-0"	7'-0"	FG	HM	T											
105A	(1)	3'-0"	7'-0"	MS	AL	IN, T											
105B	(2)	3'-0"	7'-0"	FG	HM	T								45 MIN.			
106	(1)	3'-0"	7'-0"	F	HM									45 MIN.			
107A	(1)	3'-0"	7'-0"	FG	HM	IN, T											
107B	(1)	3'-0"	7'-0"	HG	HM	T								45 MIN.			
108	(1)	3'-0"	7'-0"	F	HM												
109	(2)	3'-0"	7'-0"	F	HM												
110	(1)	3'-0"	7'-0"	F	HM												
111A	(1)	2'-8"	7'-0"	F	HM												
111B	(1)	1'-8"	7'-0"	HG	HM	T											
112	(1)	3'-0"	7'-0"	F	HM												
113A	(1)	3'-0"	7'-0"	FG	HM	T											
113B	(2) *	5'-9"	7'-0 1/8"	MS	AL	IN, T											
114A	(2)	3'-0"	7'-0"	MS	AL	IN, T											
114B	(2)	3'-0"	7'-0"	MS	AL	IN, T											


DOOR AND HARDWARE SCHEDULE ABBREVIATIONS

DOOR/FRAME MATERIALS
AL = ALUMINUM
EX = EXISTING OVERHEAD
G = GALVANIZED
HM = HOLLOW METAL
SS = STAINLESS STEEL
ST = STEEL
WD = WOOD
GLAZING TYPES
FG = FIRE GLASS
IN = INSULATED
P = 1/4" PLATE
S = SAFETY
T = TEMPERED




FRAME TYPES

NO SCALE




F

FLUSH DOOR




G

HALF GLASS DOOR




FG

FULL GLASS DOOR




L

LOUVERED DOOR




MS

MEDIUM STILE
ALUMINUM DOOR



SC2

OVERHEAD SECTIONAL
WITH FULL GLASS PANELS




FC


OVERHEAD
FIRE COILING

OVERHEAD

FINISH LEGEND




NIC



VCT



LVT



CPT



ETR

HOLLOW METAL

ALUMINUM

DOOR TYPES

NO SCALE


ROOM FINISH SCHEDULE

ROOM NO.	ROOM NAME	FLOOR	BASE	WALLS				CEILING		REMARKS
				NORTH	EAST	SOUTH	WEST	MTL	HEIGHT	
101	HANGAR BAY	SC								
102	VESTIBULE	CONC	RB-1	PT-1	PT-1	PT-1	PT-1	GWB	9'-4"	
103	EAA	CPT-1	RB-1	PT-1	PT-1	PT-1	PT-1	ACP-1	9'-4"	
104	CAP	CPT-1	RB-1	PT-1	PT-1	PT-1	PT-1	ACP-1	9'-0"	
105	MEETING ROOM	LVT-1	RB-1	PT-1	PT-1	PT-1	PT-1	GWB	SLOPED	
106	STORAGE	LVT-1	RB-1	PT-1	PT-1	PT-1	PT-1	ACP-1	9'-0"	
107	KITCHEN PREP	CT-1	CT-2	PT-1	PT-1	PT-1	PT-1	ACP-2	9'-0"	
108	ELEC	SCCPT-1	RB-1	PT-1	PT-1	PT-1	PT-1	ACP-1	9'-0"	
109	MECH.	CONC	RB-1	PT-1	PT-1	PT-1	PT-1			
110	WOMEN'S	CT-1	CT-2	CT-3/PT-1	CT-3/PT-1	CT-3/PT-1	CT-3/PT-1	GWB	9'-0"	CT-3 UP TO 4'-0"
111	JAN.	CONC	RB-1	PT-1	PT-1	PT-1	PT-1			
112	MEN'S	CT-1	CT-2	CT-3/PT-1	CT-3/PT-1	CT-3/PT-1	CT-3/PT-1	GWB	9'-0"	CT-3 UP TO 4'-0"
113	TENANT									
114	VESTIBULE	CONC	RB-1	PT-1	PT-1	PT-1	PT-1	GWB	9'-0"	
115	CORRIDOR	CT-1	RB-1	PT-1	PT-1	PT-1	PT-1	ACP-1	10'-0"	


ARCHITECTURAL FINISHES SCHEDULE

FINISH NUMBER	FINISH DESCRIPTION	PRODUCT DESCRIPTION					REMARKS
		MANUFACTURER	MODEL NUMBER	STYLE	COLOR	SIZE	
ACP-1	ACOUSTIC CEILING PANEL - TYPE 1						
ACP-2	ACOUSTIC CEILING PANEL - TYPE 2						
CPT-1	CARPET - TYPE 1						
CPT-2	CARPET - TYPE 2						
CT-1	CERAMIC TILE - TYPE 1						
CT-2	CERAMIC TILE - TYPE 2						
CT-3	CERAMIC TILE - TYPE 3						
GR-1	GROUT COLOR - TYPE 1						
PLAM-1	PLASTIC LAMINATE - TYPE 1						
PLAM-2	PLASTIC LAMINATE - TYPE 2						
PT-1	PAINT COLOR - TYPE 1						
PT-2	PAINT COLOR - TYPE 2						
RB-1	RUBBER WALL BASE - TYPE 1						
RFT-1	RUBBER FLOOR TILE - TYPE 1						
SC	SEALED CONCRETE						
SS-1	SOLID SURFACE - TYPE 1						
VCT-1	VINYL COMPOSITION TILE - TYPE 1						


3/22/2019 4:12:07 PM C:\Revit Local\2013700-171686.01-A-CENTRAL-2019_marc.goczina.rvt




9 WINDOW - W9
1/4" = 1'-0"




10 WINDOW - W10
1/4" = 1'-0"




12 WINDOW - W12
1/4" = 1'-0"




11 WINDOW - W11
1/4" = 1'-0"




6 WINDOW - W6
1/4" = 1'-0"




7 WINDOW - W7
1/4" = 1'-0"




8 WINDOW - W8
1/4" = 1'-0"




1 WINDOW - W1
1/4" = 1'-0"




2 WINDOW - W2
1/4" = 1'-0"



3 WINDOW - W3
1/4" = 1'-0"



4 WINDOW - W4
1/4" = 1'-0"



5 WINDOW - W5
1/4" = 1'-0"

C:\Revit Local\2013700-17686.01-E-CENTRAL-2019_1678mrf.rvt 3/22/2019 9:11:14 AM



TRUE PLAN
NORTH NORTH
 1
ELECTRICAL SITE PLAN
1" = 20'-0"

EQUIPMENT LAYOUTS SHOWN ARE
APPROXIMATIONS FOR PRICING. FINAL
DESIGN AND QUANTITIES MAY VARY.

**Mead
& Hunt**
Mead & Hunt, Inc.
2440 Deming Way
Middleton, WI 53562
phone: 608-273-6380
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall
not be duplicated, disclosed, or used on any
other project or extension of this project
except by written agreement with Mead &
Hunt, Inc. Mead & Hunt shall not be
responsible for any unauthorized use of, or
alteration to these documents.

**TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2**
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC
DESIGN


NOT FOR CONSTRUCTION

M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MRF
DRAWN BY: MRF
CHECKED BY: JRH
DO NOT SCALE DRAWINGS

SHEET CONTENTS
**ELECTRICAL SITE
PLAN**

SHEET NO.:

E-010



TRUE PLAN
NORTH NORTH
1
1/8" = 1'-0"
FIRST FLOOR PLAN - LIGHTING


LIGHTING GENERAL NOTES:

1. NOTES START HERE.
2. NOTES START HERE.

KEYED NOTES

EQUIPMENT LAYOUTS SHOWN ARE
APPROXIMATIONS FOR PRICING. FINAL
DESIGN AND QUANTITIES MAY VARY.

3/22/2019 9:11:17 AM C:\Revit Local\2013\700-171696.01-E-CENTRAL-2019-1678.mrf.rvt



LIGHTING GENERAL NOTES:

1. NOTES START HERE.
2. NOTES START HERE.

KEYED NOTES

EQUIPMENT LAYOUTS SHOWN ARE APPROXIMATIONS FOR PRICING. FINAL DESIGN AND QUANTITIES MAY VARY.

Mead & Hunt
Mead & Hunt, Inc.
2440 Deming Way
Middleton, WI 53562
phone: 608-273-6380
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2
10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED
03/22/19 SCHEMATIC DESIGN

NOT FOR CONSTRUCTION

MSH NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MRF
DRAWN BY: MRF
CHECKED BY: JRH

DO NOT SCALE DRAWINGS

SHEET CONTENTS
MEZZANINE PLAN - LIGHTING

SHEET NO.:

E-122

OPTIONS/ACCESSORIES CODE LISTING:

- 13
- DAMP LOCATION LISTED
- 38
- WET LOCATION LISTED

BALLAST/DRIVER CODE LISTING: (SEE SPECIFICATIONS)

- A
- LED DIMMABLE POWER SUPPLY (0-10V, 1% DIMMING).
- B
- LED DIMMABLE POWER SUPPLY (0-10V, 10% DIMMING).
- C
- LED NON-DIMMABLE POWER SUPPLY.
- D
- LED DIMMABLE POWER SUPPLY (0-10V).
- E
- LED DIMMABLE POWER SUPPLY (TRAILING EDGE).
- F
- LED DIMMABLE POWER SUPPLY 1% DIMMING LUTRON HI LUME OR EQUAL.
- G
- LED DIMMABLE POWER SUPPLY ADVANCE XITANIUM OR EQUAL.

GENERAL NOTES:

1.
- ALL LED REPLACEMENT LAMPS SHALL BE TESTED FOR DIMMING COMPATABILITY WITH DIMMING SYSTEM BEING SUPPLIED. CONTRACTOR SHALL PROVIDE MINIMUM OF (4) FOUR LAMPS OF EACH TYPE LISTED IN THIS SCHEDULE OR ANY SUBSTITUTE TO BE SUPPLIES TO DIMMING SYSTEMS/DEVICE MANUFACTURER FOR TESTING TO VERIFY LAMP PERFORMANCE.
2.
- EC SHALL VERIFY AND COORDINATE ALL LUMINAIRE TRIMS/FLANGES WITH RESPECTIVE CEILING TYPES SCHEDULED AND/OR SUBMITTED BY THE GC PRIOR TO ORDERING OF THE LUMINAIRES. SCHEDULE INDICATES TRIM TYPES BASED ON THE GENERIC CEILING INFORMATION AVAILABLE AT THE TIME BIDDING DOCUMENTS WERE ISSUED AND DOES NOT REFLECT ACTUAL THICKNESS OF GYPSUM WALL BOARD OR PLASTER CEILING OR EXACT GRID TYPE SPECIFIED BY THE ARCHITECT.

KEYED NOTES:

1.

LUMINAIRE SCHEDULE

NOTE: SEE SPECIFICATION FOR ADDITIONAL INFORMATION REGARDING LUMINAIRE AND INSTALLATION REQUIREMENTS. PROVIDE OPTIONS AND ACCESSORIES REFERENCED BY THE COLUMN TITLED " OPTIONS/ACCESSORIES". MANUFACTURERS LISTED ACCEPTABLE SHALL MEET ALL REQUIREMENTS AND FEATURES INDICATED. ACCEPTABLE MANUFACTURERS MUST MEET THE PHOTOMETRIC PERFORMANCE OF THE LISTED UNIT.

ABBREVIATIONS: GWB = GYPSUM WALL BOARD P = PENDANT R = RECESSED V = VARIES
ES = EXPOSED STRUCTURE PLAS = PLASTER S = SURFACE W = WALL MOUNTED
LG = LAY-IN GRID PL = POLE MOUNTED UNV = UNIVERSAL VOLTAGE

DES.	MANUFACTURER	CATALOG SERIES	DESCRIPTION	LAMP DATA	VOLTAGE	BALLAST/ DRIVER	MOUNT	CEILING TYPE	FIXTURE DEPTH	LED SYSTEM INPUT WATTAGE	LED DELIVERED LUMENS	OPTIONS / ACCESSORIES	ACCEPTABLE MANUFACTURERS	KEYED NOTE
A	METALUX		2' X 4' VOLUMETRIC TROFFER	LED, 4000K			R	LG			4,000			
A1	METALUX		2' X 4' LENSED GASKETED TROFFER	LED, 4000K			R	LG			5,600			
A2	METALUX		2' X 4' LENSED TROFFER	LED, 4000K			R	LG			4,200			
B	METALUX		2' X 2' VOLUMETRIC TROFFER	LED, 4000K			R	LG			3,600			
B1	METALUX		2' X 2' VOLUMETRIC TROFFER	LED, 4000K			R	GWB			3,600			
C	METALUX		1' X 4' VOLUMETRIC TROFFER	LED, 4000K			R	GWB			2,600			
D	PORTFOLIO		4" DIAMETER DOWNLIGHT	LED, 4000K			R	LG			1,500			
D1	PORTFOLIO		4" DIAMETER DOWNLIGHT WALL WASH	LED, 4000K			R	LG			1,500			
OA	HALO		4" DIAMETER EXTERIOR DOWNLIGHT, TUSCAN BRONZE TRIMS AND SOLITE LENS	LED, 3500K			R	WOOD			800	38		
OB	GARDCO		SINGLE HEAD AREA LUMINAIRE (TYPE AUTO FRONT ROW DISTRIBUTION)	LED, 4000K			W	-			9,000	38		
OC	GARDCO		SINGLE HEAD AREA LUMINAIRE (TYPE III DISTRIBUTION; 17'-6" ALUMINUM TAPERED POLE, 2'-6" HIGH BASE, 20' OVERALL HEIGHT)	LED, 4000K			PL	-			16,000	38		
P	METALUX		LENSED INDUSTRIAL HIGH BAY	LED, 4000K			P	ES			36,000			
P1	METALUX		LENSED INDUSTRIAL HIGH BAY	LED, 4000K			P	ES			20,000			
P16	AXIS LIGHTING		2-1/2" X 16' DIRECT/INDIRECT LINEAR PENDANT	LED, 4000K			P	GWB			1,000 DN 750 UP			
P10	AXIS LIGHTING		2-1/2" X 10' DIRECT/INDIRECT LINEAR PENDANT	LED, 4000K			P	GWB			1,000 DN 750 UP			
S8	METALUX		8' LENSED STRIP	LED, 4000K			S	ES			4,000			
S	METALUX		4' LENSED STRIP	LED, 4000K			S	V			2,400			
S1	METALUX		4' LENSED STRIP	LED, 4000K			P	ES			4,900			
W	TECH LIGHTING		DECORATIVE WALL MOUNTED PENDANT	LED, 4000K			W	-			750			
X1	ISOLITE		SINGLE FACE EXIT SIGN	LED			V	V			-			
X2	ISOLITE		DOUBLE FACE EXIT SIGN	LED			V	V			-			
EX/EBU	ISOLITE		EXTERIOR EMERGENCY BATTERY UNIT	LED			W	-			1,000			

EQUIPMENT LAYOUTS SHOWN ARE APPROXIMATIONS FOR PRICING. FINAL DESIGN AND QUANTITIES MAY VARY.

Mead & Hunt

Mead & Hunt, Inc.
2440 Deming Way
Middleton, WI 53562
phone: 608-273-6380
meadhunt.com

© Copyright 2019
This document, or any portion thereof, shall not be duplicated, disclosed, or used on any other project or extension of this project except by written agreement with Mead & Hunt, Inc. Mead & Hunt shall not be responsible for any unauthorized use of, or alteration to these documents.

TRUCKEE TAHOE AIRPORT
DISTRICT
HANGAR 2

10356 Truckee Airport Rd
Truckee, CA 96161

ISSUED

03/2219 SCHEMATIC
DESIGN

NOT FOR CONSTRUCTION

M&H NO.: 2013700-171696.01
DATE: March 22, 2019
DESIGNED BY: MRF
DRAWN BY: MRF
CHECKED BY: JRH

DO NOT SCALE DRAWINGS

SHEET CONTENTS
SCHEDULES

SHEET NO:

E-601